

RIVA ELITE

Name: Pearl

Width: 8"

Grade: Character



Product Description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

Composition

Structure consists of a Birch Phenolic Plywood and an Oak Plank Top Layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total Thickness (")	5/8" (16 mm)
---------------------	-----------------

Top Layer Thickness (mm)	4 mm (nominal)
--------------------------	-------------------

Plywood Thickness (mm)	12 mm
------------------------	-------

Length (ft)	6-8'
-------------	------

Width (in)	8"
------------	----

Dimensional Tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width.

Banana: 0.1% nominal length

Grade

Character Solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm) permitted. Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished

Bona® Ultra Matt Lacquer

Impact Resistance

Ø medium of deep 8.59 mm

Dimensional Stability (EN-1910):

Movement \leq 0.29%

Formaldehyde Emission (EN-120)

E0. CARB2 Comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & Impact Isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire Reaction (UNE 23727)

Cfl-S1

Profiling System

Tongue & Groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance Instructions

www.rivaspain.com



RIVA ELITE

Name: Pearl

Width: 8"

Grade: Select



Product Description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

Composition

Structure consists of a Birch Phenolic Plywood and an Oak Plank Top Layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total Thickness (") 5/8"
(16 mm)

Top Layer Thickness (mm) 4 mm
(nominal)

Plywood Thickness (mm) 12 mm

Length (ft) 6-8'

Width (in) 8"

Dimensional Tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width.

Banana: 0.1% nominal length

Grade

Select, Solid knots up to 10mm permitted in less than 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished

Bona® Ultra Matt Lacquer

Impact Resistance

Ø medium of deep 8.59 mm

Dimensional Stability (EN-1910):

Movement \leq 0.29%

Formaldehyde Emission (EN-120)

E0. CARB2 Comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & Impact Isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire Reaction (UNE 23727)

Cfl-S1

Profiling System

Tongue & Groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance Instructions

www.rivaspain.com



RIVA ELITE

Name: Cotton

Width: 8"

Grade: Character



Product Description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

Composition

Structure consists of a Birch Phenolic Plywood and an Oak Plank Top Layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total Thickness (")	5/8" (16 mm)
Top Layer Thickness (mm)	4 mm (nominal)
Plywood Thickness (mm)	12 mm
Length (ft)	6-8'
Width (in)	8"

Dimensional Tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width.

Banana: 0.1% nominal length

Grade

Character Solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm) permitted. Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished

Bona® Ultra Matt Lacquer

Impact Resistance

Ø medium of deep 8.59 mm

Dimensional Stability (EN-1910):

Movement \leq 0.29%

Formaldehyde Emission (EN-120)

E0. CARB2 Comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & Impact Isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire Reaction (UNE 23727)

Cfl-S1

Profiling System

Tongue & Groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance Instructions

www.rivaspain.com



RIVA ELITE

Name: Cotton

Width: 8"

Grade: Select



Product Description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

Composition

Structure consists of a Birch Phenolic Plywood and an Oak Plank Top Layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total Thickness (")	5/8" (16 mm)
Top Layer Thickness (mm)	4 mm (nominal)
Plywood Thickness (mm)	12 mm
Length (ft)	6-8'
Width (in)	8"

Dimensional Tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width.

Banana: 0.1% nominal length

Grade

Select, Solid knots up to 10mm permitted in less than 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished

Bona® Ultra Matt Lacquer

Impact Resistance

Ø medium of deep 8.59 mm

Dimensional Stability (EN-1910):

Movement \leq 0.29%

Formaldehyde Emission (EN-120)

E0. CARB2 Comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & Impact Isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire Reaction (UNE 23727)

Cfl-S1

Profiling System

Tongue & Groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance Instructions

www.rivaspain.com



RIVA ELITE

Name: Mercury

Width: 8"

Grade: Character



Product Description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

Composition

Structure consists of a Birch Phenolic Plywood and an Oak Plank Top Layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total Thickness (")	5/8" (16 mm)
Top Layer Thickness (mm)	4 mm (nominal)
Plywood Thickness (mm)	12 mm
Length (ft)	6-8'
Width (in)	8"

Dimensional Tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width.

Banana: 0.1% nominal length

Grade

Character Solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm) permitted. Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished

Bona® Ultra Matt Lacquer

Impact Resistance

Ø medium of deep 8.59 mm

Dimensional Stability (EN-1910):

Movement \leq 0.29%

Formaldehyde Emission (EN-120)

E0. CARB2 Comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & Impact Isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire Reaction (UNE 23727)

Cfl-S1

Profiling System

Tongue & Groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance Instructions

www.rivaspain.com



RIVA ELITE

Name: Mercury

Width: 8"

Grade: Select



Product Description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

Composition

Structure consists of a Birch Phenolic Plywood and an Oak Plank Top Layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total Thickness (") 5/8"
(16 mm)

Top Layer Thickness (mm) 4 mm
(nominal)

Plywood Thickness (mm) 12 mm

Length (ft) 6-8'

Width (in) 8"

Dimensional Tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width.

Banana: 0.1% nominal length

Grade

Select, Solid knots up to 10mm permitted in less than 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished

Bona® Ultra Matt Lacquer

Impact Resistance

Ø medium of deep 8.59 mm

Dimensional Stability (EN-1910):

Movement \leq 0.29%

Formaldehyde Emission (EN-120)

E0. CARB2 Comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & Impact Isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire Reaction (UNE 23727)

Cfl-S1

Profiling System

Tongue & Groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance Instructions

www.rivaspain.com



RIVA ELITE

Name: Smoke

Width: 8"

Grade: Character



Product Description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

Composition

Structure consists of a Birch Phenolic Plywood and an Oak Plank Top Layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total Thickness (")	5/8" (16 mm)
Top Layer Thickness (mm)	4 mm (nominal)
Plywood Thickness (mm)	12 mm
Length (ft)	6-8'
Width (in)	8"

Dimensional Tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width.

Banana: 0.1% nominal length

Grade

Character Solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm) permitted. Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished

Bona® Ultra Matt Lacquer

Impact Resistance

Ø medium of deep 8.59 mm

Dimensional Stability (EN-1910):

Movement \leq 0.29%

Formaldehyde Emission (EN-120)

E0. CARB2 Comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & Impact Isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire Reaction (UNE 23727)

Cfl-S1

Profiling System

Tongue & Groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance Instructions

www.rivaspain.com



RIVA ELITE

Name: Smoke

Width: 8"

Grade: Select



Product Description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

Composition

Structure consists of a Birch Phenolic Plywood and an Oak Plank Top Layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total Thickness (")	5/8" (16 mm)
---------------------	-----------------

Top Layer Thickness (mm)	4 mm (nominal)
--------------------------	-------------------

Plywood Thickness (mm)	12 mm
------------------------	-------

Length (ft)	6-8'
-------------	------

Width (in)	8"
------------	----

Dimensional Tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width.

Banana: 0.1% nominal length

Grade

Select, Solid knots up to 10mm permitted in less than 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished

Bona® Ultra Matt Lacquer

Impact Resistance

Ø medium of deep 8.59 mm

Dimensional Stability (EN-1910):

Movement \leq 0.29%

Formaldehyde Emission (EN-120)

E0. CARB2 Comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & Impact Isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire Reaction (UNE 23727)

Cfl-S1

Profiling System

Tongue & Groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance Instructions

www.rivaspain.com



RIVA ELITE

Name: Sand

Width: 8"

Grade: Character



Product Description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

Composition

Structure consists of a Birch Phenolic Plywood and an Oak Plank Top Layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total Thickness (")	5/8" (16 mm)
Top Layer Thickness (mm)	4 mm (nominal)
Plywood Thickness (mm)	12 mm
Length (ft)	6-8'
Width (in)	8"

Dimensional Tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width.

Banana: 0.1% nominal length

Grade

Character Solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm) permitted. Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished

Bona® Ultra Matt Lacquer

Impact Resistance

Ø medium of deep 8.59 mm

Dimensional Stability (EN-1910):

Movement \leq 0.29%

Formaldehyde Emission (EN-120)

E0. CARB2 Comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & Impact Isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire Reaction (UNE 23727)

Cfl-S1

Profiling System

Tongue & Groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance Instructions

www.rivaspain.com



RIVA ELITE

Name: Sand

Width: 8"

Grade: Select



Product Description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

Composition

Structure consists of a Birch Phenolic Plywood and an Oak Plank Top Layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total Thickness (")	5/8" (16 mm)
Top Layer Thickness (mm)	4 mm (nominal)
Plywood Thickness (mm)	12 mm
Length (ft)	6-8'
Width (in)	8"

Dimensional Tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width.

Banana: 0.1% nominal length

Grade

Select, Solid knots up to 10mm permitted in less than 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished

Bona® Ultra Matt Lacquer

Impact Resistance

Ø medium of deep 8.59 mm

Dimensional Stability (EN-1910):

Movement \leq 0.29%

Formaldehyde Emission (EN-120)

E0. CARB2 Comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & Impact Isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire Reaction (UNE 23727)

Cfl-S1

Profiling System

Tongue & Groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance Instructions

www.rivaspain.com



RIVA ELITE

Name: Earth

Width: 8"

Grade: Character



Product Description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

Composition

Structure consists of a Birch Phenolic Plywood and an Oak Plank Top Layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total Thickness (")	5/8" (16 mm)
---------------------	-----------------

Top Layer Thickness (mm)	4 mm (nominal)
--------------------------	-------------------

Plywood Thickness (mm)	12 mm
------------------------	-------

Length (ft)	6-8'
-------------	------

Width (in)	8"
------------	----

Dimensional Tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width.

Banana: 0.1% nominal length

Grade

Character Solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm) permitted. Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished

Bona® Ultra Matt Lacquer

Impact Resistance

Ø medium of deep 8.59 mm

Dimensional Stability (EN-1910):

Movement \leq 0.29%

Formaldehyde Emission (EN-120)

E0. CARB2 Comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & Impact Isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire Reaction (UNE 23727)

Cfl-S1

Profiling System

Tongue & Groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance Instructions

www.rivaspain.com



RIVA ELITE

Name: Earth

Width: 8"

Grade: Select



Product Description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

Composition

Structure consists of a Birch Phenolic Plywood and an Oak Plank Top Layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total Thickness (")	5/8" (16 mm)
Top Layer Thickness (mm)	4 mm (nominal)
Plywood Thickness (mm)	12 mm
Length (ft)	6-8'
Width (in)	8"

Dimensional Tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width.

Banana: 0.1% nominal length

Grade

Select, Solid knots up to 10mm permitted in less than 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished

Bona® Ultra Matt Lacquer

Impact Resistance

Ø medium of deep 8.59 mm

Dimensional Stability (EN-1910):

Movement \leq 0.29%

Formaldehyde Emission (EN-120)

E0. CARB2 Comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & Impact Isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire Reaction (UNE 23727)

Cfl-S1

Profiling System

Tongue & Groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance Instructions

www.rivaspain.com



RIVA ELITE

Name: Crystal

Width: 8"

Grade: Character



Product Description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

Composition

Structure consists of a Birch Phenolic Plywood and an Oak Plank Top Layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total Thickness (")	5/8" (16 mm)
Top Layer Thickness (mm)	4 mm (nominal)
Plywood Thickness (mm)	12 mm
Length (ft)	6-8'
Width (in)	8"

Dimensional Tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width.

Banana: 0.1% nominal length

Grade

Character Solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm) permitted. Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished

Bona® Ultra Matt Lacquer

Impact Resistance

Ø medium of deep 8.59 mm

Dimensional Stability (EN-1910):

Movement \leq 0.29%

Formaldehyde Emission (EN-120)

E0. CARB2 Comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & Impact Isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire Reaction (UNE 23727)

Cfl-S1

Profiling System

Tongue & Groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance Instructions

www.rivaspain.com



RIVA ELITE

Name: Crystal

Width: 8"

Grade: Select



Product Description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

Composition

Structure consists of a Birch Phenolic Plywood and an Oak Plank Top Layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total Thickness (")	5/8" (16 mm)
Top Layer Thickness (mm)	4 mm (nominal)
Plywood Thickness (mm)	12 mm
Length (ft)	6-8'
Width (in)	8"

Dimensional Tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width.

Banana: 0.1% nominal length

Grade

Select, Solid knots up to 10mm permitted in less than 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished

Bona® Ultra Matt Lacquer

Impact Resistance

Ø medium of deep 8.59 mm

Dimensional Stability (EN-1910):

Movement \leq 0.29%

Formaldehyde Emission (EN-120)

E0. CARB2 Comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & Impact Isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire Reaction (UNE 23727)

Cfl-S1

Profiling System

Tongue & Groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance Instructions

www.rivaspain.com



RIVA ELITE

Name: Krypton

Width: 8"

Grade: Character



Product Description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

Composition

Structure consists of a Birch Phenolic Plywood and an Oak Plank Top Layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total Thickness (")	5/8" (16 mm)
Top Layer Thickness (mm)	4 mm (nominal)
Plywood Thickness (mm)	12 mm
Length (ft)	6-8'
Width (in)	8"

Dimensional Tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width.

Banana: 0.1% nominal length

Grade

Character Solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm) permitted. Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished

Bona® Ultra Matt Lacquer

Impact Resistance

Ø medium of deep 8.59 mm

Dimensional Stability (EN-1910):

Movement \leq 0.29%

Formaldehyde Emission (EN-120)

E0. CARB2 Comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & Impact Isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire Reaction (UNE 23727)

Cfl-S1

Profiling System

Tongue & Groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance Instructions

www.rivaspain.com



RIVA ELITE

Name: Krypton

Width: 8"

Grade: Select



Product Description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

Composition

Structure consists of a Birch Phenolic Plywood and an Oak Plank Top Layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total Thickness (")	5/8" (16 mm)
Top Layer Thickness (mm)	4 mm (nominal)
Plywood Thickness (mm)	12 mm
Length (ft)	6-8'
Width (in)	8"

Dimensional Tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width.

Banana: 0.1% nominal length

Grade

Select, Solid knots up to 10mm permitted in less than 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished

Bona® Ultra Matt Lacquer

Impact Resistance

Ø medium of deep 8.59 mm

Dimensional Stability (EN-1910):

Movement \leq 0.29%

Formaldehyde Emission (EN-120)

E0. CARB2 Comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & Impact Isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire Reaction (UNE 23727)

Cfl-S1

Profiling System

Tongue & Groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance Instructions

www.rivaspain.com



RIVA ELITE

Name: Amber

Width: 8"

Grade: Character



Product Description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

Composition

Structure consists of a Birch Phenolic Plywood and an Oak Plank Top Layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total Thickness (")	5/8" (16 mm)
Top Layer Thickness (mm)	4 mm (nominal)
Plywood Thickness (mm)	12 mm
Length (ft)	6-8'
Width (in)	8"

Dimensional Tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width.

Banana: 0.1% nominal length

Grade

Character Solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm) permitted. Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished

Bona® Ultra Matt Lacquer

Impact Resistance

Ø medium of deep 8.59 mm

Dimensional Stability (EN-1910):

Movement \leq 0.29%

Formaldehyde Emission (EN-120)

E0. CARB2 Comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & Impact Isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire Reaction (UNE 23727)

Cfl-S1

Profiling System

Tongue & Groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance Instructions

www.rivaspain.com



RIVA ELITE

Name: Amber

Width: 8"

Grade: Select



Product Description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

Composition

Structure consists of a Birch Phenolic Plywood and an Oak Plank Top Layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total Thickness (")	5/8" (16 mm)
Top Layer Thickness (mm)	4 mm (nominal)
Plywood Thickness (mm)	12 mm
Length (ft)	6-8'
Width (in)	8"

Dimensional Tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width.

Banana: 0.1% nominal length

Grade

Select, Solid knots up to 10mm permitted in less than 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished

Bona® Ultra Matt Lacquer

Impact Resistance

Ø medium of deep 8.59 mm

Dimensional Stability (EN-1910):

Movement \leq 0.29%

Formaldehyde Emission (EN-120)

E0. CARB2 Comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & Impact Isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire Reaction (UNE 23727)

Cfl-S1

Profiling System

Tongue & Groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance Instructions

www.rivaspain.com



RIVA ELITE

Name: Cigar

Width: 8"

Grade: Character



Product Description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

Composition

Structure consists of a Birch Phenolic Plywood and an Oak Plank Top Layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total Thickness (") 5/8"
(16 mm)

Top Layer Thickness (mm) 4 mm
(nominal)

Plywood Thickness (mm) 12 mm

Length (ft) 6-8'

Width (in) 8"

Dimensional Tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width.

Banana: 0.1% nominal length

Grade

Character Solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm) permitted. Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished

Bona® Ultra Matt Lacquer

Impact Resistance

Ø medium of deep 8.59 mm

Dimensional Stability (EN-1910):

Movement \leq 0.29%

Formaldehyde Emission (EN-120)

E0. CARB2 Comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & Impact Isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire Reaction (UNE 23727)

Cfl-S1

Profiling System

Tongue & Groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance Instructions

www.rivaspain.com



RIVA ELITE

Name: Cigar

Width: 8"

Grade: Select



Product Description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

Composition

Structure consists of a Birch Phenolic Plywood and an Oak Plank Top Layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total Thickness (")	5/8" (16 mm)
Top Layer Thickness (mm)	4 mm (nominal)
Plywood Thickness (mm)	12 mm
Length (ft)	6-8'
Width (in)	8"

Dimensional Tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width.

Banana: 0.1% nominal length

Grade

Select, Solid knots up to 10mm permitted in less than 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished

Bona® Ultra Matt Lacquer

Impact Resistance

Ø medium of deep 8.59 mm

Dimensional Stability (EN-1910):

Movement \leq 0.29%

Formaldehyde Emission (EN-120)

E0. CARB2 Comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & Impact Isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire Reaction (UNE 23727)

Cfl-S1

Profiling System

Tongue & Groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance Instructions

www.rivaspain.com



RIVA ELITE

Name: Gray

Width: 8"

Grade: Character



Product Description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

Composition

Structure consists of a Birch Phenolic Plywood and an Oak Plank Top Layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total Thickness (") 5/8"
(16 mm)

Top Layer Thickness (mm) 4 mm
(nominal)

Plywood Thickness (mm) 12 mm

Length (ft) 6-8'

Width (in) 8"

Dimensional Tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width.

Banana: 0.1% nominal length

Grade

Character Solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm) permitted. Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished

Bona® Ultra Matt Lacquer

Impact Resistance

Ø medium of deep 8.59 mm

Dimensional Stability (EN-1910):

Movement \leq 0.29%

Formaldehyde Emission (EN-120)

E0. CARB2 Comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & Impact Isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire Reaction (UNE 23727)

Cfl-S1

Profiling System

Tongue & Groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance Instructions

www.rivaspain.com



RIVA ELITE

Name: Gray

Width: 8"

Grade: Select



Product Description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

Composition

Structure consists of a Birch Phenolic Plywood and an Oak Plank Top Layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total Thickness (")	5/8" (16 mm)
Top Layer Thickness (mm)	4 mm (nominal)
Plywood Thickness (mm)	12 mm
Length (ft)	6-8'
Width (in)	8"

Dimensional Tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width.

Banana: 0.1% nominal length

Grade

Select, Solid knots up to 10mm permitted in less than 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished

Bona® Ultra Matt Lacquer

Impact Resistance

Ø medium of deep 8.59 mm

Dimensional Stability (EN-1910):

Movement \leq 0.29%

Formaldehyde Emission (EN-120)

E0. CARB2 Comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & Impact Isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire Reaction (UNE 23727)

Cfl-S1

Profiling System

Tongue & Groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance Instructions

www.rivaspain.com



RIVA ELITE

Name: Black

Width: 8"

Grade: Character



Product Description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

Composition

Structure consists of a Birch Phenolic Plywood and an Oak Plank Top Layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total Thickness (")	5/8" (16 mm)
Top Layer Thickness (mm)	4 mm (nominal)
Plywood Thickness (mm)	12 mm
Length (ft)	6-8'
Width (in)	8"

Dimensional Tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width.

Banana: 0.1% nominal length

Grade

Character Solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm) permitted. Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished

Bona® Ultra Matt Lacquer

Impact Resistance

Ø medium of deep 8.59 mm

Dimensional Stability (EN-1910):

Movement \leq 0.29%

Formaldehyde Emission (EN-120)

E0. CARB2 Comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & Impact Isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire Reaction (UNE 23727)

Cfl-S1

Profiling System

Tongue & Groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance Instructions

www.rivaspain.com



RIVA ELITE

Name: Black
Width: 8"
Grade: Select



Product Description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

Composition

Structure consists of a Birch Phenolic Plywood and an Oak Plank Top Layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total Thickness (")	5/8" (16 mm)
Top Layer Thickness (mm)	4 mm (nominal)
Plywood Thickness (mm)	12 mm
Length (ft)	6-8'
Width (in)	8"

Dimensional Tolerances (EN 13647)

Length: Nominal \pm 0.1%
Width: Nominal \pm 0.2%
Cupping: 0.2% of nominal width.
Banana: 0.1% nominal length

Grade

Select, Solid knots up to 10mm permitted in less than 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished

Bona® Ultra Matt Lacquer

Impact Resistance

Ø medium of deep 8.59 mm

Dimensional Stability (EN-1910):

Movement \leq 0.29%

Formaldehyde Emission (EN-120)

E0. CARB2 Comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & Impact Isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire Reaction (UNE 23727)

Cfl-S1

Profiling System

Tongue & Groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance Instructions

www.rivaspain.com

