

LA RIVA

Name: LA RIVA

Width: 8"

Color: Phantom

Grade: Select



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 5/8"
(16 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 12 mm

Length (ft) 8'

Width (in) 8"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Select, solid knots up to 10mm permitted in less than 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tongue & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 8"

Color: Phantom

Grade: Character



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 5/8"
(16 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 12 mm

Length (ft) 8'

Width (in) 8"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm) permitted. Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tonge & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 10"

Color: Phantom

Grade: Select



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 5/8"
(16 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 12 mm

Length (ft) 8'

Width (in) 10"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Select, solid knots up to 10mm permitted in less than 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tongue & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 10"

Color: Phantom

Grade: Character



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 5/8"
(16 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 12 mm

Length (ft) 8'

Width (in) 10"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm) permitted. Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910):

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tonge & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 12"

Color: Phantom

Grade: Select



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 3/4"
(19 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 15 mm

Length (ft) 8'

Width (in) 12"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Select, solid knots up to 10mm permitted in less than 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tonge & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 12"

Color: Phantom

Grade: Character



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 3/4"
(19 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 15 mm

Length (ft) 8'

Width (in) 12"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm) permitted. Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tonge & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 14"

Color: Phantom

Grade: Select



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 3/4"
(19 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 15 mm

Length (ft) 8'

Width (in) 14"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Select, solid knots up to 10mm permitted in less than 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tongue & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 14"

Color: Phantom

Grade: Character



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 3/4"
(19 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 15 mm

Length (ft) 8'

Width (in) 14"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm) permitted. Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tonge & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 8"

Color: Azure

Grade: Select



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 5/8"
(16 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 12 mm

Length (ft) 8'

Width (in) 8"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Select, solid knots up to 10mm permitted in less than 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tongue & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 8"

Color: Azure

Grade: Character



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 5/8"
(16 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 12 mm

Length (ft) 8'

Width (in) 8"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm) permitted. Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tonge & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 10"

Color: Azure

Grade: Select



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 5/8"
(16 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 12 mm

Length (ft) 8'

Width (in) 10"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Select, solid knots up to 10mm permitted in less than 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tongue & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 10"

Color: Azure

Grade: Character



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 5/8"
(16 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 12 mm

Length (ft) 8'

Width (in) 10"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm) permitted. Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910):

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tonge & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 12"

Color: Azure

Grade: Select



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 3/4"
(19 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 15 mm

Length (ft) 8'

Width (in) 12"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Select, solid knots up to 10mm permitted in less than 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tongue & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 12"

Color: Azure

Grade: Character



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 3/4"
(19 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 15 mm

Length (ft) 8'

Width (in) 12"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm) permitted. Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tonge & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 14"

Color: Azure

Grade: Select



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 3/4"
(19 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 15 mm

Length (ft) 8'

Width (in) 14"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Select, solid knots up to 10mm permitted in less than 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

ΔL_w : 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tongue & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 14"

Color: Azure

Grade: Character



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 3/4"
(19 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 15 mm

Length (ft) 8'

Width (in) 14"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm) permitted. Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tonge & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 8"

Color: Veyron

Grade: Select



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 5/8"
(16 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 12 mm

Length (ft) 8'

Width (in) 8"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Select, solid knots up to 10mm permitted in less than 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tongue & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 8"

Color: Veyron

Grade: Character



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 5/8"
(16 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 12 mm

Length (ft) 8'

Width (in) 8"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm) permitted. Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tonge & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 10"

Color: Veyron

Grade: Select



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 5/8"
(16 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 12 mm

Length (ft) 8'

Width (in) 10"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Select, solid knots up to 10mm permitted in less than 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tonge & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 10"

Color: Veyron

Grade: Character



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 5/8"
(16 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 12 mm

Length (ft) 8'

Width (in) 10"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm) permitted. Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910):

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tonge & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 12"

Color: Veyron

Grade: Select



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 3/4"
(19 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 15 mm

Length (ft) 8'

Width (in) 12"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Select, solid knots up to 10mm permitted in less than 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tongue & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 12"

Color: Veyron

Grade: Character



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 3/4"
(19 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 15 mm

Length (ft) 8'

Width (in) 12"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm) permitted. Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tonge & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 14"

Color: Veyron

Grade: Select



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 3/4"
(19 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 15 mm

Length (ft) 8'

Width (in) 14"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Select, solid knots up to 10mm permitted in less than 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tongue & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 14"

Color: Veyron

Grade: Character



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 3/4"
(19 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 15 mm

Length (ft) 8'

Width (in) 14"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm) permitted. Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tonge & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 8"

Color: Carrera

Grade: Select



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 5/8"
(16 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 12 mm

Length (ft) 8'

Width (in) 8"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Select, solid knots up to 10mm permitted in less than 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tongue & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 8"

Color: Carrera

Grade: Character



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 5/8"
(16 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 12 mm

Length (ft) 8'

Width (in) 8"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm) permitted. Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tonge & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 10"

Color: Carrera

Grade: Select



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 5/8"
(16 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 12 mm

Length (ft) 8'

Width (in) 10"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Select, solid knots up to 10mm permitted in less than 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tongue & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 10"

Color: Carrera

Grade: Character



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 5/8"
(16 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 12 mm

Length (ft) 8'

Width (in) 10"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm) permitted. Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910):

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tongue & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 12"

Color: Carrera

Grade: Select



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 3/4"
(19 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 15 mm

Length (ft) 8'

Width (in) 12"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Select, solid knots up to 10mm permitted in less than 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tongue & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 12"

Color: Carrera

Grade: Character



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 3/4"
(19 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 15 mm

Length (ft) 8'

Width (in) 12"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm) permitted. Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tongue & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 14"

Color: Carrera

Grade: Select



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 3/4"
(19 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 15 mm

Length (ft) 8'

Width (in) 14"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Select, solid knots up to 10mm permitted in less than 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tongue & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 14"

Color: Carrera

Grade: Character



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 3/4"
(19 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 15 mm

Length (ft) 8'

Width (in) 14"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm) permitted. Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tonge & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 8"

Color: Monza

Grade: Select



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 5/8"
(16 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 12 mm

Length (ft) 8'

Width (in) 8"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Select, solid knots up to 10mm permitted in less than 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tongue & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 8"

Color: Monza

Grade: Character



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 5/8"
(16 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 12 mm

Length (ft) 8'

Width (in) 8"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm) permitted. Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tonge & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 10"

Color: Monza

Grade: Select



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 5/8"
(16 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 12 mm

Length (ft) 8'

Width (in) 10"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Select, solid knots up to 10mm permitted in less than 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tongue & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 10"

Color: Monza

Grade: Character



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 5/8"
(16 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 12 mm

Length (ft) 8'

Width (in) 10"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm) permitted. Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910):

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

ΔL_w : 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tonge & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 12"

Color: Monza

Grade: Select



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 3/4"
(19 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 15 mm

Length (ft) 8'

Width (in) 12"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Select, solid knots up to 10mm permitted in less than 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tongue & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 12"

Color: Monza

Grade: Character



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 3/4"
(19 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 15 mm

Length (ft) 8'

Width (in) 12"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm) permitted. Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tonge & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 14"

Color: Monza

Grade: Select



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 3/4"
(19 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 15 mm

Length (ft) 8'

Width (in) 14"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Select, solid knots up to 10mm permitted in less than 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tongue & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 14"

Color: Monza

Grade: Character



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 3/4"
(19 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 15 mm

Length (ft) 8'

Width (in) 14"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm) permitted. Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tonge & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 8"

Color: Huracan

Grade: Select



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 5/8"
(16 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 12 mm

Length (ft) 8'

Width (in) 8"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Select, solid knots up to 10mm permitted in less than 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

ΔL_w : 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tongue & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 8"

Color: Huracan

Grade: Character



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 5/8"
(16 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 12 mm

Length (ft) 8'

Width (in) 8"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm) permitted. Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tonge & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 10"

Color: Huracan

Grade: Select



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 5/8"
(16 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 12 mm

Length (ft) 8'

Width (in) 10"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Select, solid knots up to 10mm permitted in less than 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tongue & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 10"

Color: Huracan

Grade: Character



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 5/8"
(16 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 12 mm

Length (ft) 8'

Width (in) 10"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm) permitted. Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910):

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

ΔL_w : 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tonge & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 12"

Color: Huracan

Grade: Select



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 3/4"
(19 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 15 mm

Length (ft) 8'

Width (in) 12"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Select, solid knots up to 10mm permitted in less than 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tongue & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 12"

Color: Huracan

Grade: Character



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 3/4"
(19 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 15 mm

Length (ft) 8'

Width (in) 12"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm) permitted. Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tonge & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 14"

Color: Huracan

Grade: Select



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 3/4"
(19 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 15 mm

Length (ft) 8'

Width (in) 14"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Select, solid knots up to 10mm permitted in less than 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tonge & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 14"

Color: Huracan

Grade: Character



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 3/4"
(19 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 15 mm

Length (ft) 8'

Width (in) 14"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm) permitted. Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tonge & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 8"

Color: Urus

Grade: Select



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 5/8"
(16 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 12 mm

Length (ft) 8'

Width (in) 8"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Select, solid knots up to 10mm permitted in less than 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tongue & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 8"

Color: Urus

Grade: Character



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 5/8"
(16 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 12 mm

Length (ft) 8'

Width (in) 8"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm) permitted. Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tonge & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 10"

Color: Urus

Grade: Select



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 5/8"
(16 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 12 mm

Length (ft) 8'

Width (in) 10"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Select, solid knots up to 10mm permitted in less than 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tonge & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 10"

Color: Urus

Grade: Character



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 5/8"
(16 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 12 mm

Length (ft) 8'

Width (in) 10"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm) permitted. Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910):

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

ΔL_w : 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tongue & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 12"

Color: Urus

Grade: Select



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 3/4"
(19 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 15 mm

Length (ft) 8'

Width (in) 12"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Select, solid knots up to 10mm permitted in less than 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tongue & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 12"

Color: Urus

Grade: Character



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 3/4"
(19 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 15 mm

Length (ft) 8'

Width (in) 12"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm) permitted. Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tonge & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 14"

Color: Urus

Grade: Select



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 3/4"
(19 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 15 mm

Length (ft) 8'

Width (in) 14"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Select, solid knots up to 10mm permitted in less than 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tonge & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 14"

Color: Urus

Grade: Character



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 3/4"
(19 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 15 mm

Length (ft) 8'

Width (in) 14"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm) permitted. Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tonge & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 8"

Color: Enzo

Grade: Select



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 5/8"
(16 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 12 mm

Length (ft) 8'

Width (in) 8"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Select, solid knots up to 10mm permitted in less than 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tongue & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 8"

Color: Enzo

Grade: Character



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 5/8"
(16 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 12 mm

Length (ft) 8'

Width (in) 8"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm) permitted. Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tonge & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 10"

Color: Enzo

Grade: Select



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 5/8"
(16 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 12 mm

Length (ft) 8'

Width (in) 10"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Select, solid knots up to 10mm permitted in less than 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tongue & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 10"

Color: Enzo

Grade: Character



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 5/8"
(16 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 12 mm

Length (ft) 8'

Width (in) 10"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm) permitted. Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910):

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tonge & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 12"

Color: Enzo

Grade: Select



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 3/4"
(19 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 15 mm

Length (ft) 8'

Width (in) 12"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Select, solid knots up to 10mm permitted in less than 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tongue & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 12"

Color: Enzo

Grade: Character



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 3/4"
(19 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 15 mm

Length (ft) 8'

Width (in) 12"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm) permitted. Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tonge & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 14"

Color: Enzo

Grade: Select



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 3/4"
(19 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 15 mm

Length (ft) 8'

Width (in) 14"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Select, solid knots up to 10mm permitted in less than 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tongue & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN



LA RIVA

Name: LA RIVA

Width: 14"

Color: Enzo

Grade: Character



Product description

This product has been manufactured according to the European Norm EN13489. Product: Multilayer parquet oak plank.

Composition

Structure consists of a birch phenolic plywood and an oak plank top layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

Dimensions

Total thickness (") 3/4"
(19 mm)

Top layer thickness (mm) 4 mm
(nominal)

Plywood thickness (mm) 15 mm

Length (ft) 8'

Width (in) 14"

Dimensional tolerances (EN 13647)

Length: Nominal \pm 0.1%

Width: Nominal \pm 0.2%

Cupping: 0.2% of nominal width

Banana: 0.1% nominal length

Grade

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm) permitted. Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Color variation

Reactive stains work by reacting with the natural tannins found in wood to create extremely unique and rich tones, impossible to achieve by traditional staining methods. Due to the nature of the reactive staining process, there is an inherent color variation to be expected with every plank, because every plank has its own particular levels of tannins.

Finished

UV oil & reactive stains

Impact resistance

Ø medium of deep 8.59 mm

Dimensional stability (EN-1910)

Movement \leq 0.29%

Formaldehyde emission (EN-120)

E0. CARB2 comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & impact isolation (UNE-EN-ISO 140-8)

Δ Lw: 17 dB

Fire reaction (UNE 23727)

Cfl-S1

Profiling system

Tonge & groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance instructions

www.rivaspain.com

WWW.RIVASPAIN.COM

RIVA
SPAIN

