



**Pearl**                      **10" x 60"**                      **Select**  
 Color                      Size                      Grade

**Porcelain Tile**  
 Construction



**TECHNICAL CHARACTERISTICS**

<b>Fabrication process</b>	Dry pressed porcelain tile	<b>Work size (mm)</b>	247 x 1500 x 11
<b>Absorption group ISO 13006</b>	Bla	<b>Aesthetic classification and shade variations</b>	V.2
<b>Finish</b>	GL	<b>Different design number</b>	48
<b>Rectified</b>	Yes	<b>Facial dimension range and surface quality</b>	Complies with the standard
<b>Body</b>	STD Body		

**PHYSICAL CHARACTERISTICS**

<b>Water absorption</b>	$E \leq 0.5$	UNE EN ISO 10545-3
<b>Braking strength (S)</b>	$> 1300N$	UNE EN ISO 10545-4
<b>Flexural tensile strength (N/mm<sup>2</sup>)</b>	$\geq 35 N/mm^2$	UNE EN ISO 10545-4
<b>Resistance to superficial abrasion (PEI)</b>	4	UNE EN ISO 10545-7
<b>Lineal thermal expansion between 20°C to 100° C</b>	Complies with the standard	UNE EN ISO 10545-8
<b>Thermic shock resistance</b>	Complies with the standard	UNE EN ISO 10545-9
<b>Crazing resistance</b>	Complies with the standard	UNE EN ISO 10545-11
<b>Durability; Freeze - thaw cycle</b>	Complies with the standard	UNE EN ISO 10545-12
<b>Scratch hardness according to Mohs</b>	5	UNE EN 67-101-92
<b>Slipperiness</b>	Anti-slip Class 1	UNE 41901 EX
	Anti-slip R.9	DIN 51130
	Anti-slip Class B	DIN 51097

**CHEMICAL PROPERTIES**

<b>Resistance to home cleaning products and swimming pool salts</b>	Complies with the standard	UNE EN ISO 10545-13
<b>Resistance to high concentration acids and bases</b>	Minimum HB	UNE EN ISO 10545-13
<b>Resistance to low concentration acids and bases</b>	Minimum LB	UNE EN ISO 10545-13
<b>Resistance to staining</b>	Complies with the standard	UNE EN ISO 10545-14

**Important notes:**

Before fixing tiles, please check the shade, calibre and choice. Claims regarding these items cannot be accepted once the materials have been fixed. Protecting the product during placement and appropriate cleaning after grouting and other work are part of a correct fitting process. For more information visit our website: [www.rivaspain.com](http://www.rivaspain.com) The stated weight is approximate, it may vary up to 5% depending on the model, the variation may be greater for products with relief. Document with commercial information and cannot be used either judicially or administratively without the express permission of RIVA Spain. The color of the tile of this technical data is for guidance only and may differ from the actual tile color.

**CE marking**



004CPR-PR/11-4-2013

**Certifications**



**Cotton**                      **10" x 60"**                      **Select**  
Color                              Size                                      Grade

**Porcelain Tile**  
Construction



## TECHNICAL CHARACTERISTICS

<b>Fabrication process</b>	Dry pressed porcelain tile	<b>Work size (mm)</b>	247 x 1500 x 11
<b>Absorption group ISO 13006</b>	Bla	<b>Aesthetic classification and shade variations</b>	V.2
<b>Finish</b>	GL	<b>Different design number</b>	48
<b>Rectified</b>	Yes	<b>Facial dimension range and surface quality</b>	Complies with the standard
<b>Body</b>	STD Body		

## PHYSICAL CHARACTERISTICS

<b>Water absorption</b>	$E \leq 0.5$	UNE EN ISO 10545-3
<b>Braking strength (S)</b>	$> 1300N$	UNE EN ISO 10545-4
<b>Flexural tensile strength (N/mm<sup>2</sup>)</b>	$\geq 35 N/mm^2$	UNE EN ISO 10545-4
<b>Resistance to superficial abrasion (PEI)</b>	4	UNE EN ISO 10545-7
<b>Lineal thermal expansion between 20°C to 100° C</b>	Complies with the standard	UNE EN ISO 10545-8
<b>Thermic shock resistance</b>	Complies with the standard	UNE EN ISO 10545-9
<b>Crazing resistance</b>	Complies with the standard	UNE EN ISO 10545-11
<b>Durability; Freeze - thaw cycle</b>	Complies with the standard	UNE EN ISO 10545-12
<b>Scratch hardness according to Mohs</b>	5	UNE EN 67-101-92
<b>Slipperiness</b>	Anti-slip Class 1	UNE 41901 EX
	Anti-slip R.9	DIN 51130
	Anti-slip Class B	DIN 51097

## CHEMICAL PROPERTIES

<b>Resistance to home cleaning products and swimming pool salts</b>	Complies with the standard	UNE EN ISO 10545-13
<b>Resistance to high concentration acids and bases</b>	Minimum HB	UNE EN ISO 10545-13
<b>Resistance to low concentration acids and bases</b>	Minimum LB	UNE EN ISO 10545-13
<b>Resistance to staining</b>	Complies with the standard	UNE EN ISO 10545-14

## Important notes:

Before fixing tiles, please check the shade, calibre and choice. Claims regarding these items cannot be accepted once the materials have been fixed. Protecting the product during placement and appropriate cleaning after grouting and other work are part of a correct fitting process. For more information visit our website: [www.rivaspain.com](http://www.rivaspain.com) The stated weight is approximate, it may vary up to 5% depending on the model, the variation may be greater for products with relief. Document with commercial information and cannot be used either judicially or administratively without the express permission of RIVA Spain. The color of the tile of this technical data is for guidance only and may differ from the actual tile color.

CE marking



004CPR-PR/11-4-2013

Certifications





**Crystal**      **10" x 60"**      **Select**  
 Color            Size                    Grade

**Porcelain Tile**  
 Construction



**TECHNICAL CHARACTERISTICS**

<b>Fabrication process</b>	Dry pressed porcelain tile	<b>Work size (mm)</b>	247 x 1500 x 11
<b>Absorption group ISO 13006</b>	Bla	<b>Aesthetic classification and shade variations</b>	V.2
<b>Finish</b>	GL	<b>Different design number</b>	48
<b>Rectified</b>	Yes	<b>Facial dimension range and surface quality</b>	Complies with the standard
<b>Body</b>	STD Body		

**PHYSICAL CHARACTERISTICS**

<b>Water absorption</b>	$E \leq 0.5$	UNE EN ISO 10545-3
<b>Braking strength (S)</b>	$> 1300N$	UNE EN ISO 10545-4
<b>Flexural tensile strength (N/mm<sup>2</sup>)</b>	$\geq 35 N/mm^2$	UNE EN ISO 10545-4
<b>Resistance to superficial abrasion (PEI)</b>	4	UNE EN ISO 10545-7
<b>Lineal thermal expansion between 20°C to 100° C</b>	Complies with the standard	UNE EN ISO 10545-8
<b>Thermic shock resistance</b>	Complies with the standard	UNE EN ISO 10545-9
<b>Crazing resistance</b>	Complies with the standard	UNE EN ISO 10545-11
<b>Durability; Freeze - thaw cycle</b>	Complies with the standard	UNE EN ISO 10545-12
<b>Scratch hardness according to Mohs</b>	5	UNE EN 67-101-92
<b>Slipperiness</b>	Anti-slip Class 1	UNE 41901 EX
	Anti-slip R.9	DIN 51130
	Anti-slip Class B	DIN 51097

**CHEMICAL PROPERTIES**

<b>Resistance to home cleaning products and swimming pool salts</b>	Complies with the standard	UNE EN ISO 10545-13
<b>Resistance to high concentration acids and bases</b>	Minimum HB	UNE EN ISO 10545-13
<b>Resistance to low concentration acids and bases</b>	Minimum LB	UNE EN ISO 10545-13
<b>Resistance to staining</b>	Complies with the standard	UNE EN ISO 10545-14

**Important notes:**

Before fixing tiles, please check the shade, calibre and choice. Claims regarding these items cannot be accepted once the materials have been fixed. Protecting the product during placement and appropriate cleaning after grouting and other work are part of a correct fitting process. For more information visit our website: [www.rivaspain.com](http://www.rivaspain.com) The stated weight is approximate, it may vary up to 5% depending on the model, the variation may be greater for products with relief. Document with commercial information and cannot be used either judicially or administratively without the express permission of RIVA Spain. The color of the tile of this technical data is for guidance only and may differ from the actual tile color.

**CE marking**



004CPR-PR/11-4-2013

**Certifications**



**Sand**                      **10" x 60"**                      **Select**  
 Color                      Size                      Grade

**Porcelain Tile**  
 Construction



## TECHNICAL CHARACTERISTICS

<b>Fabrication process</b>	Dry pressed porcelain tile	<b>Work size (mm)</b>	247 x 1500 x 11
<b>Absorption group ISO 13006</b>	Bla	<b>Aesthetic classification and shade variations</b>	V.2
<b>Finish</b>	GL	<b>Different design number</b>	48
<b>Rectified</b>	Yes	<b>Facial dimension range and surface quality</b>	Complies with the standard
<b>Body</b>	STD Body		

## PHYSICAL CHARACTERISTICS

<b>Water absorption</b>	$E \leq 0.5$	UNE EN ISO 10545-3
<b>Braking strength (S)</b>	$> 1300N$	UNE EN ISO 10545-4
<b>Flexural tensile strength (N/mm<sup>2</sup>)</b>	$\geq 35 N/mm^2$	UNE EN ISO 10545-4
<b>Resistance to superficial abrasion (PEI)</b>	4	UNE EN ISO 10545-7
<b>Lineal thermal expansion between 20°C to 100° C</b>	Complies with the standard	UNE EN ISO 10545-8
<b>Thermic shock resistance</b>	Complies with the standard	UNE EN ISO 10545-9
<b>Crazing resistance</b>	Complies with the standard	UNE EN ISO 10545-11
<b>Durability; Freeze - thaw cycle</b>	Complies with the standard	UNE EN ISO 10545-12
<b>Scratch hardness according to Mohs</b>	5	UNE EN 67-101-92
<b>Slipperiness</b>	Anti-slip Class 1 Anti-slip R.9 Anti-slip Class B	UNE 41901 EX DIN 51130 DIN 51097

## CHEMICAL PROPERTIES

<b>Resistance to home cleaning products and swimming pool salts</b>	Complies with the standard	UNE EN ISO 10545-13
<b>Resistance to high concentration acids and bases</b>	Minimum HB	UNE EN ISO 10545-13
<b>Resistance to low concentration acids and bases</b>	Minimum LB	UNE EN ISO 10545-13
<b>Resistance to staining</b>	Complies with the standard	UNE EN ISO 10545-14

## Important notes:

Before fixing tiles, please check the shade, calibre and choice. Claims regarding these items cannot be accepted once the materials have been fixed. Protecting the product during placement and appropriate cleaning after grouting and other work are part of a correct fitting process. For more information visit our website: [www.rivaspain.com](http://www.rivaspain.com) The stated weight is approximate, it may vary up to 5% depending on the model, the variation may be greater for products with relief. Document with commercial information and cannot be used either judicially or administratively without the express permission of RIVA Spain. The color of the tile of this technical data is for guidance only and may differ from the actual tile color.

CE marking



004CPR-PR/11-4-2013

Certifications



Smoke  
Color

10" x 60"  
Size

Select  
Grade

Porcelain Tile  
Construction



## TECHNICAL CHARACTERISTICS

<b>Fabrication process</b>	Dry pressed porcelain tile	<b>Work size (mm)</b>	247 x 1500 x 11
<b>Absorption group ISO 13006</b>	Bla	<b>Aesthetic classification and shade variations</b>	V.2
<b>Finish</b>	GL	<b>Different design number</b>	48
<b>Rectified</b>	Yes	<b>Facial dimension range and surface quality</b>	Complies with the standard
<b>Body</b>	STD Body		

## PHYSICAL CHARACTERISTICS

<b>Water absorption</b>	$E \leq 0.5$	UNE EN ISO 10545-3
<b>Braking strength (S)</b>	$> 1300N$	UNE EN ISO 10545-4
<b>Flexural tensile strength (N/mm<sup>2</sup>)</b>	$\geq 35 N/mm^2$	UNE EN ISO 10545-4
<b>Resistance to superficial abrasion (PEI)</b>	4	UNE EN ISO 10545-7
<b>Lineal thermal expansion between 20°C to 100° C</b>	Complies with the standard	UNE EN ISO 10545-8
<b>Thermic shock resistance</b>	Complies with the standard	UNE EN ISO 10545-9
<b>Crazing resistance</b>	Complies with the standard	UNE EN ISO 10545-11
<b>Durability; Freeze - thaw cycle</b>	Complies with the standard	UNE EN ISO 10545-12
<b>Scratch hardness according to Mohs</b>	5	UNE EN 67-101-92
<b>Slipperiness</b>	Anti-slip Class 1 Anti-slip R.9 Anti-slip Class B	UNE 41901 EX DIN 51130 DIN 51097

## CHEMICAL PROPERTIES

<b>Resistance to home cleaning products and swimming pool salts</b>	Complies with the standard	UNE EN ISO 10545-13
<b>Resistance to high concentration acids and bases</b>	Minimum HB	UNE EN ISO 10545-13
<b>Resistance to low concentration acids and bases</b>	Minimum LB	UNE EN ISO 10545-13
<b>Resistance to staining</b>	Complies with the standard	UNE EN ISO 10545-14

## Important notes:

Before fixing tiles, please check the shade, calibre and choice. Claims regarding these items cannot be accepted once the materials have been fixed. Protecting the product during placement and appropriate cleaning after grouting and other work are part of a correct fitting process. For more information visit our website: [www.rivaspain.com](http://www.rivaspain.com) The stated weight is approximate, it may vary up to 5% depending on the model, the variation may be greater for products with relief. Document with commercial information and cannot be used either judicially or administratively without the express permission of RIVA Spain. The color of the tile of this technical data is for guidance only and may differ from the actual tile color.

CE marking



004CPR-PR/11-4-2013

Certifications





**Earth**                      **10" x 60"**                      **Select**  
 Color                      Size                      Grade

**Porcelain Tile**  
 Construction

## TECHNICAL CHARACTERISTICS

<b>Fabrication process</b>	Dry pressed porcelain tile	<b>Work size (mm)</b>	247 x 1500 x 11
<b>Absorption group ISO 13006</b>	Bla	<b>Aesthetic classification and shade variations</b>	V.2
<b>Finish</b>	GL	<b>Different design number</b>	48
<b>Rectified</b>	Yes	<b>Facial dimension range and surface quality</b>	Complies with the standard
<b>Body</b>	STD Body		

## PHYSICAL CHARACTERISTICS

<b>Water absorption</b>	$E \leq 0.5$	UNE EN ISO 10545-3
<b>Braking strength (S)</b>	$> 1300N$	UNE EN ISO 10545-4
<b>Flexural tensile strength (N/mm<sup>2</sup>)</b>	$\geq 35 N/mm^2$	UNE EN ISO 10545-4
<b>Resistance to superficial abrasion (PEI)</b>	4	UNE EN ISO 10545-7
<b>Lineal thermal expansion between 20°C to 100° C</b>	Complies with the standard	UNE EN ISO 10545-8
<b>Thermic shock resistance</b>	Complies with the standard	UNE EN ISO 10545-9
<b>Crazing resistance</b>	Complies with the standard	UNE EN ISO 10545-11
<b>Durability; Freeze - thaw cycle</b>	Complies with the standard	UNE EN ISO 10545-12
<b>Scratch hardness according to Mohs</b>	5	UNE EN 67-101-92
<b>Slipperiness</b>	Anti-slip Class 1 Anti-slip R.9 Anti-slip Class B	UNE 41901 EX DIN 51130 DIN 51097

## CHEMICAL PROPERTIES

<b>Resistance to home cleaning products and swimming pool salts</b>	Complies with the standard	UNE EN ISO 10545-13
<b>Resistance to high concentration acids and bases</b>	Minimum HB	UNE EN ISO 10545-13
<b>Resistance to low concentration acids and bases</b>	Minimum LB	UNE EN ISO 10545-13
<b>Resistance to staining</b>	Complies with the standard	UNE EN ISO 10545-14

## Important notes:

Before fixing tiles, please check the shade, calibre and choice. Claims regarding these items cannot be accepted once the materials have been fixed. Protecting the product during placement and appropriate cleaning after grouting and other work are part of a correct fitting process. For more information visit our website: [www.rivaspain.com](http://www.rivaspain.com) The stated weight is approximate, it may vary up to 5% depending on the model, the variation may be greater for products with relief. Document with commercial information and cannot be used either judicially or administratively without the express permission of RIVA Spain. The color of the tile of this technical data is for guidance only and may differ from the actual tile color.

CE marking



004CPR-PR/11-4-2013

Certifications





**Amber**                      **10" x 60"**                      **Select**  
 Color                              Size                                      Grade

**Porcelain Tile**  
 Construction

**TECHNICAL CHARACTERISTICS**

<b>Fabrication process</b>	Dry pressed porcelain tile	<b>Work size (mm)</b>	247 x 1500 x 11
<b>Absorption group ISO 13006</b>	Bla	<b>Aesthetic classification and shade variations</b>	V.2
<b>Finish</b>	GL	<b>Different design number</b>	48
<b>Rectified</b>	Yes	<b>Facial dimension range and surface quality</b>	Complies with the standard
<b>Body</b>	STD Body		

**PHYSICAL CHARACTERISTICS**

<b>Water absorption</b>	$E \leq 0.5$	UNE EN ISO 10545-3
<b>Braking strength (S)</b>	$> 1300N$	UNE EN ISO 10545-4
<b>Flexural tensile strength (N/mm<sup>2</sup>)</b>	$\geq 35 N/mm^2$	UNE EN ISO 10545-4
<b>Resistance to superficial abrasion (PEI)</b>	4	UNE EN ISO 10545-7
<b>Lineal thermal expansion between 20°C to 100° C</b>	Complies with the standard	UNE EN ISO 10545-8
<b>Thermic shock resistance</b>	Complies with the standard	UNE EN ISO 10545-9
<b>Crazing resistance</b>	Complies with the standard	UNE EN ISO 10545-11
<b>Durability; Freeze - thaw cycle</b>	Complies with the standard	UNE EN ISO 10545-12
<b>Scratch hardness according to Mohs</b>	5	UNE EN 67-101-92
<b>Slipperiness</b>	Anti-slip Class 1	UNE 41901 EX
	Anti-slip R.9	DIN 51130
	Anti-slip Class B	DIN 51097

**CHEMICAL PROPERTIES**

<b>Resistance to home cleaning products and swimming pool salts</b>	Complies with the standard	UNE EN ISO 10545-13
<b>Resistance to high concentration acids and bases</b>	Minimum HB	UNE EN ISO 10545-13
<b>Resistance to low concentration acids and bases</b>	Minimum LB	UNE EN ISO 10545-13
<b>Resistance to staining</b>	Complies with the standard	UNE EN ISO 10545-14

**Important notes:**

Before fixing tiles, please check the shade, calibre and choice. Claims regarding these items cannot be accepted once the materials have been fixed. Protecting the product during placement and appropriate cleaning after grouting and other work are part of a correct fitting process. For more information visit our website: [www.rivaspain.com](http://www.rivaspain.com) The stated weight is approximate, it may vary up to 5% depending on the model, the variation may be greater for products with relief. Document with commercial information and cannot be used either judicially or administratively without the express permission of RIVA Spain. The color of the tile of this technical data is for guidance only and may differ from the actual tile color.

**CE marking**



004CPR-PR/11-4-2013

**Certifications**

