

# TIERRA

NOBLE & NATURAL

**Mar** **8"** **Character**  
Name Width Grade



## DESCRIPTION

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

## COMPOSITION

Structure consists of a Baltic Birch Plywood and European White Oak, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

## DIMENSIONS

Total thickness (in)	9/16" (14mm)
Top Layer thickness (mm)	3 mm (nominal)
Plywood thickness (mm)	11 mm
Length (ft)	6-8'
Width (in)	8"

## DIMENSIONS TOLERANCES (EN 13647)

Length	Nominal $\pm$ 0.1%
Width	Nominal $\pm$ 0.2%
Cupping	0.2% of nominal width
Banana	0.1% nominal length

## GRADE

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm). Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished	Bona® Ultra Matt Lacquer
Impact Resistance	Ø medium of deep 8.59 mm
Dimensional Stability (EN-1910):	Movement $\leq$ 0.29%
Formaldehyde Emission (EN-120)	E0. CARB2 Comply
Thermal conductivity (UNE-92-202)	0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8)	$\Delta$ Lw: 17 dB
Fire Reaction (UNE 23727)	Cfl-S1
Profiling System	Tongue & Groove, beveled 2 sides
Warranty	<a href="http://www.rivaspain.com">www.rivaspain.com</a>
Maintenance Instructions	<a href="http://www.rivaspain.com">www.rivaspain.com</a>



# TIERRA

NOBLE & NATURAL

**Cielo**                      **8"**                      **Character**  
 Name                      Width                      Grade



## DESCRIPTION

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

## COMPOSITION

Structure consists of a Baltic Birch Plywood and European White Oak, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

## DIMENSIONS

<b>Total thickness (in)</b>	9/16" (14mm)
<b>Top Layer thickness (mm)</b>	3 mm (nominal)
<b>Plywood thickness (mm)</b>	11 mm
<b>Length (ft)</b>	6-8'
<b>Width (in)</b>	8"

## DIMENSIONS TOLERANCES (EN 13647)

<b>Length</b>	Nominal ± 0.1%
<b>Width</b>	Nominal ± 0.2%
<b>Cupping</b>	0.2% of nominal width
<b>Banana</b>	0.1% nominal length

## GRADE

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm). Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

<b>Finished</b>	Bona® Ultra Matt Lacquer
<b>Impact Resistance</b>	Ø medium of deep 8.59 mm
<b>Dimensional Stability (EN-1910):</b>	Movement ≤ 0.29%
<b>Formaldehyde Emission (EN-120)</b>	E0. CARB2 Comply
<b>Thermal conductivity (UNE-92-202)</b>	0.14W/moK
<b>Noise &amp; Impact Isolation (UNE-EN-ISO 140-8)</b>	ΔLw: 17 dB
<b>Fire Reaction (UNE 23727)</b>	Cfl-S1
<b>Profiling System</b>	Tongue & Groove, beveled 2 sides
<b>Warranty</b>	<a href="http://www.rivaspain.com">www.rivaspain.com</a>
<b>Maintenance Instructions</b>	<a href="http://www.rivaspain.com">www.rivaspain.com</a>



# TIERRA

NOBLE & NATURAL

**Sol** **8"** **Character**  
 Name Width Grade



## DESCRIPTION

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

## COMPOSITION

Structure consists of a Baltic Birch Plywood and European White Oak, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

## DIMENSIONS

<b>Total thickness (in)</b>	9/16" (14mm)
<b>Top Layer thickness (mm)</b>	3 mm (nominal)
<b>Plywood thickness (mm)</b>	11 mm
<b>Length (ft)</b>	6-8'
<b>Width (in)</b>	8"

## DIMENSIONS TOLERANCES (EN 13647)

<b>Length</b>	Nominal ± 0.1%
<b>Width</b>	Nominal ± 0.2%
<b>Cupping</b>	0.2% of nominal width
<b>Banana</b>	0.1% nominal length

## GRADE

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm). Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

<b>Finished</b>	Bona® Ultra Matt Lacquer
<b>Impact Resistance</b>	Ø medium of deep 8.59 mm
<b>Dimensional Stability (EN-1910):</b>	Movement ≤ 0.29%
<b>Formaldehyde Emission (EN-120)</b>	E0. CARB2 Comply
<b>Thermal conductivity (UNE-92-202)</b>	0.14W/moK
<b>Noise &amp; Impact Isolation (UNE-EN-ISO 140-8)</b>	ΔLw: 17 dB
<b>Fire Reaction (UNE 23727)</b>	Cfl-S1
<b>Profiling System</b>	Tongue & Groove, beveled 2 sides
<b>Warranty</b>	<a href="http://www.rivaspain.com">www.rivaspain.com</a>
<b>Maintenance Instructions</b>	<a href="http://www.rivaspain.com">www.rivaspain.com</a>



# TIERRA

NOBLE & NATURAL

**Arena**                      **8"**                      **Character**  
 Name                      Width                      Grade



## DESCRIPTION

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

## COMPOSITION

Structure consists of a Baltic Birch Plywood and European White Oak, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

## DIMENSIONS

<b>Total thickness (in)</b>	9/16" (14mm)
<b>Top Layer thickness (mm)</b>	3 mm (nominal)
<b>Plywood thickness (mm)</b>	11 mm
<b>Length (ft)</b>	6-8'
<b>Width (in)</b>	8"

## DIMENSIONS TOLERANCES (EN 13647)

<b>Length</b>	Nominal ± 0.1%
<b>Width</b>	Nominal ± 0.2%
<b>Cupping</b>	0.2% of nominal width
<b>Banana</b>	0.1% nominal length

## GRADE

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm). Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

<b>Finished</b>	Bona® Ultra Matt Lacquer
<b>Impact Resistance</b>	Ø medium of deep 8.59 mm
<b>Dimensional Stability (EN-1910):</b>	Movement ≤ 0.29%
<b>Formaldehyde Emission (EN-120)</b>	E0. CARB2 Comply
<b>Thermal conductivity (UNE-92-202)</b>	0.14W/moK
<b>Noise &amp; Impact Isolation (UNE-EN-ISO 140-8)</b>	ΔLw: 17 dB
<b>Fire Reaction (UNE 23727)</b>	Cfl-S1
<b>Profiling System</b>	Tongue & Groove, beveled 2 sides
<b>Warranty</b>	<a href="http://www.rivaspain.com">www.rivaspain.com</a>
<b>Maintenance Instructions</b>	<a href="http://www.rivaspain.com">www.rivaspain.com</a>



# TIERRA

NOBLE & NATURAL

**Monte** **8"** **Character**  
 Name Width Grade



## DESCRIPTION

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

## COMPOSITION

Structure consists of a Baltic Birch Plywood and European White Oak, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

## DIMENSIONS

<b>Total thickness (in)</b>	9/16" (14mm)
<b>Top Layer thickness (mm)</b>	3 mm (nominal)
<b>Plywood thickness (mm)</b>	11 mm
<b>Length (ft)</b>	6-8'
<b>Width (in)</b>	8"

## DIMENSIONS TOLERANCES (EN 13647)

<b>Length</b>	Nominal ± 0.1%
<b>Width</b>	Nominal ± 0.2%
<b>Cupping</b>	0.2% of nominal width
<b>Banana</b>	0.1% nominal length

## GRADE

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm). Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

<b>Finished</b>	Bona® Ultra Matt Lacquer
<b>Impact Resistance</b>	Ø medium of deep 8.59 mm
<b>Dimensional Stability (EN-1910):</b>	Movement ≤ 0.29%
<b>Formaldehyde Emission (EN-120)</b>	E0. CARB2 Comply
<b>Thermal conductivity (UNE-92-202)</b>	0.14W/moK
<b>Noise &amp; Impact Isolation (UNE-EN-ISO 140-8)</b>	ΔLw: 17 dB
<b>Fire Reaction (UNE 23727)</b>	Cfl-S1
<b>Profiling System</b>	Tongue & Groove, beveled 2 sides
<b>Warranty</b>	<a href="http://www.rivaspain.com">www.rivaspain.com</a>
<b>Maintenance Instructions</b>	<a href="http://www.rivaspain.com">www.rivaspain.com</a>

