

Mar **7 1/2"**
Name Width

Select
Grade

DESCRIPTION

Product: Multilayer Parquet Oak Plank.



COMPOSITION

Structure consists of a Baltic Birch Plywood and White Oak, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

DIMENSIONS

Total thickness (in)	5/8" (15mm)
Top Layer thickness (mm)	4 mm (nominal)
Plywood thickness (mm)	11 mm
Length	75" - 75% fixed lengths
Width (in)	7 1/2"

DIMENSIONS TOLERANCES

Length	Nominal \pm 0.1%
Width	Nominal \pm 0.2%
Cupping	0.2% of nominal width
Banana	0.1% nominal length

GRADE

Select, solid knots up to 10 mm permitted in less 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished	Germany Treffert Lacquer
Impact Resistance	\varnothing medium of deep 8.59 mm
Dimensional Stability (EN-1910):	Movement \leq 0.29%
Formaldehyde Emission (EN-120)	EO. CARB2 Comply
Thermal conductivity (UNE-92-202)	0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8)	$\Delta Lw: 17$ dB
Fire Reaction (UNE 23727)	Cfl-S1
Profiling System	Tongue & Groove, beveled 2 sides
Warranty	www.rivaspain.com
Maintenance Instructions	www.rivaspain.com



Cielo **7 1/2"** Select
Name Width Grade

DESCRIPTION

Product: Multilayer Parquet Oak Plank.



COMPOSITION

Structure consists of a Baltic Birch Plywood and White Oak, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

DIMENSIONS

Total thickness (in)	5/8" (15mm)
Top Layer thickness (mm)	4 mm (nominal)
Plywood thickness (mm)	11 mm
Length	75" - 75% fixed lengths
Width (in)	7 1/2"

DIMENSIONS TOLERANCES

Length	Nominal \pm 0.1%
Width	Nominal \pm 0.2%
Cupping	0.2% of nominal width
Banana	0.1% nominal length

GRADE

Select, solid knots up to 10 mm permitted in less 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished	Germany Treffert Lacquer
Impact Resistance	\varnothing medium of deep 8.59 mm
Dimensional Stability (EN-1910):	Movement \leq 0.29%
Formaldehyde Emission (EN-120)	EO. CARB2 Comply
Thermal conductivity (UNE-92-202)	0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8)	Δ Lw: 17 dB
Fire Reaction (UNE 23727)	Cfl-S1
Profiling System	Tongue & Groove, beveled 2 sides
Warranty	www.rivaspain.com
Maintenance Instructions	www.rivaspain.com



Sol Name **7 1/2"** Width Select Grade

DESCRIPTION

Product: Multilayer Parquet Oak Plank.



COMPOSITION

Structure consists of a Baltic Birch Plywood and White Oak, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

DIMENSIONS

Total thickness (in)	5/8" (15mm)
Top Layer thickness (mm)	4 mm (nominal)
Plywood thickness (mm)	11 mm
Length	75" - 75% fixed lengths
Width (in)	7 1/2"

DIMENSIONS TOLERANCES

Length	Nominal \pm 0.1%
Width	Nominal \pm 0.2%
Cupping	0.2% of nominal width
Banana	0.1% nominal length

GRADE

Select, solid knots up to 10 mm permitted in less 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished	Germany Treffert Lacquer
Impact Resistance	Ø medium of deep 8.59 mm
Dimensional Stability (EN-1910):	Movement \leq 0.29%
Formaldehyde Emission (EN-120)	EO. CARB2 Comply
Thermal conductivity (UNE-92-202)	0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8)	$\Delta Lw: 17$ dB
Fire Reaction (UNE 23727)	Cfl-S1
Profiling System	Tongue & Groove, beveled 2 sides
Warranty	www.rivaspain.com
Maintenance Instructions	www.rivaspain.com



Arena **7 1/2"**
Name Width

Select
Grade



DESCRIPTION

Product: Multilayer Parquet Oak Plank.

COMPOSITION

Structure consists of a Baltic Birch Plywood and White Oak, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

DIMENSIONS

Total thickness (in)	5/8" (15mm)
Top Layer thickness (mm)	4 mm (nominal)
Plywood thickness (mm)	11 mm
Length	75" - 75% fixed lengths
Width (in)	7 1/2"

DIMENSIONS TOLERANCES

Length	Nominal \pm 0.1%
Width	Nominal \pm 0.2%
Cupping	0.2% of nominal width
Banana	0.1% nominal length

GRADE

Select, solid knots up to 10 mm permitted in less 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished	Germany Treffert Lacquer
Impact Resistance	\varnothing medium of deep 8.59 mm
Dimensional Stability (EN-1910):	Movement \leq 0.29%
Formaldehyde Emission (EN-120)	EO. CARB2 Comply
Thermal conductivity (UNE-92-202)	0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8)	$\Delta Lw: 17$ dB
Fire Reaction (UNE 23727)	Cfl-S1
Profiling System	Tongue & Groove, beveled 2 sides
Warranty	www.rivaspain.com
Maintenance Instructions	www.rivaspain.com



Monte **7 1/2"**
Name Width

Select
Grade

DESCRIPTION

Product: Multilayer Parquet Oak Plank.



COMPOSITION

Structure consists of a Baltic Birch Plywood and White Oak, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

DIMENSIONS

Total thickness (in)	5/8" (15mm)
Top Layer thickness (mm)	4 mm (nominal)
Plywood thickness (mm)	11 mm
Length	75" - 75% fixed lengths
Width (in)	7 1/2"

DIMENSIONS TOLERANCES

Length	Nominal \pm 0.1%
Width	Nominal \pm 0.2%
Cupping	0.2% of nominal width
Banana	0.1% nominal length

GRADE

Select, solid knots up to 10 mm permitted in less 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished	Germany Treffert Lacquer
Impact Resistance	\varnothing medium of deep 8.59 mm
Dimensional Stability (EN-1910):	Movement \leq 0.29%
Formaldehyde Emission (EN-120)	EO. CARB2 Comply
Thermal conductivity (UNE-92-202)	0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8)	Δ Lw: 17 dB
Fire Reaction (UNE 23727)	Cfl-S1
Profiling System	Tongue & Groove, beveled 2 sides
Warranty	www.rivaspain.com
Maintenance Instructions	www.rivaspain.com

