

RIVA\MAX

Pearl 10" Prime
Color Width Grade



DESCRIPTION

This product has been manufactured in Spain in accordance with the European standard EN13489. Product: Multi-Layered Engineered Hardwood Floor

COMPOSITION

Engineered for superior stability and durability, the structure combines a high-performance Marine-Grade Phenolic Birch Plywood core with a premium European Oak top layer. Both layers are bonded with polyvinyl acetate adhesives in accordance with CARB Phase 2 compliance standards.

DIMENSIONS

Total thickness (in) 5/8"
Top Layer thickness (mm) 4 mm (nominal)
Plywood thickness (mm) 12 mm
Length (ft) 6 - 8'
Width (in) 8"

DIMENSIONS TOLERANCES (EN 13647)

Length Nominal ± 0.1%
Width Nominal ± 0.2%
Cupping 0.2% of nominal width
Banana 0.1% nominal length

Length	6'	6.5'	7.2'	8'
Weight / box (lb)	33.85	35.10	37.60	47.60
Sq.ft. / box	15.75	17.5	19.22	21.41
Boxes / pallet	60	60	60	60
Weight / pallet	2085	2160	2310	2910
Sq.ft. / pallet	945	1050	1153.2	1284.6

GRADE

Prime, solid knots up to 10 mm permitted in less 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished Bona® Ultra Matt Lacquer
Impact Resistance Ø medium of deep 8.59 mm
Dimensional Stability (EN-1910): Movement ≤ 0.29%
Formaldehyde Emission (EN-120) E0. CARB2 Comply
Thermal conductivity (UNE-92-202) 0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8) ΔLw: 17 dB
Fire Reaction (UNE 23727) Cfl-S1
Profiling System Tongue & Groove, beveled 2 sides
Warranty www.rivaspain.com
Maintenance & Instructions www.rivaspain.com



RIVA\MAX

Pearl 10" Character
Color Width Grade



DESCRIPTION

This product has been manufactured in Spain in accordance with the European standard EN13489. Product: Multi-Layered Engineered Hardwood Floor

COMPOSITION

Engineered for superior stability and durability, the structure combines a high-performance Marine-Grade Phenolic Birch Plywood core with a premium European Oak top layer. Both layers are bonded with polyvinyl acetate adhesives in accordance with CARB Phase 2 compliance standards.

DIMENSIONS

Total thickness (in) 5/8"
Top Layer thickness (mm) 4 mm (nominal)
Plywood thickness (mm) 12 mm
Length (ft) 6 - 8'
Width (in) 8"

DIMENSIONS TOLERANCES (EN 13647)

Length Nominal ± 0.1%
Width Nominal ± 0.2%
Cupping 0.2% of nominal width
Banana 0.1% nominal length

Length	6'	6.5'	7.2'	8'
Weight / box (lb)	33.85	35.10	37.60	47.60
Sq.ft. / box	15.75	17.5	19.22	21.41
Boxes / pallet	60	60	60	60
Weight / pallet	2085	2160	2310	2910
Sq.ft. / pallet	945	1050	1153.2	1284.6

GRADE

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm). Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished Bona® Ultra Matt Lacquer
Impact Resistance Ø medium of deep 8.59 mm
Dimensional Stability (EN-1910): Movement ≤ 0.29%
Formaldehyde Emission (EN-120) E0. CARB2 Comply
Thermal conductivity (UNE-92-202) 0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8) ΔLw: 17 dB
Fire Reaction (UNE 23727) Cfl-S1
Profiling System Tongue & Groove, beveled 2 sides
Warranty www.rivaspain.com
Maintenance & Instructions www.rivaspain.com



RIVA\MAX

Crystal 10" Prime
Color Width Grade



DESCRIPTION

This product has been manufactured in Spain in accordance with the European standard EN13489. Product: Multi-Layered Engineered Hardwood Floor

COMPOSITION

Engineered for superior stability and durability, the structure combines a high-performance Marine-Grade Phenolic Birch Plywood core with a premium European Oak top layer. Both layers are bonded with polyvinyl acetate adhesives in accordance with CARB Phase 2 compliance standards.

DIMENSIONS

Total thickness (in) 5/8"
Top Layer thickness (mm) 4 mm (nominal)
Plywood thickness (mm) 12 mm
Length (ft) 6 - 8'
Width (in) 8"

DIMENSIONS TOLERANCES (EN 13647)

Length Nominal ± 0.1%
Width Nominal ± 0.2%
Cupping 0.2% of nominal width
Banana 0.1% nominal length

Length	6'	6.5'	7.2'	8'
Weight / box (lb)	33.85	35.10	37.60	47.60
Sq.ft. / box	15.75	17.5	19.22	21.41
Boxes / pallet	60	60	60	60
Weight / pallet	2085	2160	2310	2910
Sq.ft. / pallet	945	1050	1153.2	1284.6

GRADE

Prime, solid knots up to 10 mm permitted in less 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished Bona® Ultra Matt Lacquer
Impact Resistance Ø medium of deep 8.59 mm
Dimensional Stability (EN-1910): Movement ≤ 0.29%
Formaldehyde Emission (EN-120) E0. CARB2 Comply
Thermal conductivity (UNE-92-202) 0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8) ΔLw: 17 dB
Fire Reaction (UNE 23727) Cfl-S1
Profiling System Tongue & Groove, beveled 2 sides
Warranty www.rivaspain.com
Maintenance & Instructions www.rivaspain.com



RIVA\MAX

Crystal 10" Character
Color Width Grade



DESCRIPTION

This product has been manufactured in Spain in accordance with the European standard EN13489. Product: Multi-Layered Engineered Hardwood Floor

COMPOSITION

Engineered for superior stability and durability, the structure combines a high-performance Marine-Grade Phenolic Birch Plywood core with a premium European Oak top layer. Both layers are bonded with polyvinyl acetate adhesives in accordance with CARB Phase 2 compliance standards.

DIMENSIONS

Total thickness (in) 5/8"
Top Layer thickness (mm) 4 mm (nominal)
Plywood thickness (mm) 12 mm
Length (ft) 6 - 8'
Width (in) 8"

DIMENSIONS TOLERANCES (EN 13647)

Length Nominal ± 0.1%
Width Nominal ± 0.2%
Cupping 0.2% of nominal width
Banana 0.1% nominal length

Length	6'	6.5'	7.2'	8'
Weight / box (lb)	33.85	35.10	37.60	47.60
Sq.ft. / box	15.75	17.5	19.22	21.41
Boxes / pallet	60	60	60	60
Weight / pallet	2085	2160	2310	2910
Sq.ft. / pallet	945	1050	1153.2	1284.6

GRADE

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm). Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished Bona® Ultra Matt Lacquer
Impact Resistance Ø medium of deep 8.59 mm
Dimensional Stability (EN-1910): Movement ≤ 0.29%
Formaldehyde Emission (EN-120) E0. CARB2 Comply
Thermal conductivity (UNE-92-202) 0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8) ΔLw: 17 dB
Fire Reaction (UNE 23727) Cfl-S1
Profiling System Tongue & Groove, beveled 2 sides
Warranty www.rivaspain.com
Maintenance & Instructions www.rivaspain.com



RIVA\MAX

Cotton 10" Prime
Color Width Grade



DESCRIPTION

This product has been manufactured in Spain in accordance with the European standard EN13489. Product: Multi-Layered Engineered Hardwood Floor

COMPOSITION

Engineered for superior stability and durability, the structure combines a high-performance Marine-Grade Phenolic Birch Plywood core with a premium European Oak top layer. Both layers are bonded with polyvinyl acetate adhesives in accordance with CARB Phase 2 compliance standards.

DIMENSIONS

Total thickness (in) 5/8"
Top Layer thickness (mm) 4 mm (nominal)
Plywood thickness (mm) 12 mm
Length (ft) 6 - 8'
Width (in) 8"

DIMENSIONS TOLERANCES (EN 13647)

Length Nominal ± 0.1%
Width Nominal ± 0.2%
Cupping 0.2% of nominal width
Banana 0.1% nominal length

Length	6'	6.5'	7.2'	8'
Weight / box (lb)	33.85	35.10	37.60	47.60
Sq.ft. / box	15.75	17.5	19.22	21.41
Boxes / pallet	60	60	60	60
Weight / pallet	2085	2160	2310	2910
Sq.ft. / pallet	945	1050	1153.2	1284.6

GRADE

Prime, solid knots up to 10 mm permitted in less 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished Bona® Ultra Matt Lacquer
Impact Resistance Ø medium of deep 8.59 mm
Dimensional Stability (EN-1910): Movement ≤ 0.29%
Formaldehyde Emission (EN-120) E0. CARB2 Comply
Thermal conductivity (UNE-92-202) 0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8) ΔLw: 17 dB
Fire Reaction (UNE 23727) Cfl-S1
Profiling System Tongue & Groove, beveled 2 sides
Warranty www.rivaspain.com
Maintenance & Instructions www.rivaspain.com



RIVA\MAX

Cotton 10" Character
Color Width Grade



DESCRIPTION

This product has been manufactured in Spain in accordance with the European standard EN13489. Product: Multi-Layered Engineered Hardwood Floor

COMPOSITION

Engineered for superior stability and durability, the structure combines a high-performance Marine-Grade Phenolic Birch Plywood core with a premium European Oak top layer. Both layers are bonded with polyvinyl acetate adhesives in accordance with CARB Phase 2 compliance standards.

DIMENSIONS

Total thickness (in) 5/8"
Top Layer thickness (mm) 4 mm (nominal)
Plywood thickness (mm) 12 mm
Length (ft) 6 - 8'
Width (in) 8"

DIMENSIONS TOLERANCES (EN 13647)

Length Nominal ± 0.1%
Width Nominal ± 0.2%
Cupping 0.2% of nominal width
Banana 0.1% nominal length

Length	6'	6.5'	7.2'	8'
Weight / box (lb)	33.85	35.10	37.60	47.60
Sq.ft. / box	15.75	17.5	19.22	21.41
Boxes / pallet	60	60	60	60
Weight / pallet	2085	2160	2310	2910
Sq.ft. / pallet	945	1050	1153.2	1284.6

GRADE

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm). Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished Bona® Ultra Matt Lacquer
Impact Resistance Ø medium of deep 8.59 mm
Dimensional Stability (EN-1910): Movement ≤ 0.29%
Formaldehyde Emission (EN-120) E0. CARB2 Comply
Thermal conductivity (UNE-92-202) 0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8) ΔLw: 17 dB
Fire Reaction (UNE 23727) Cfl-S1
Profiling System Tongue & Groove, beveled 2 sides
Warranty www.rivaspain.com
Maintenance & Instructions www.rivaspain.com



RIVA\MAX

Smoke 10" Prime
Color Width Grade



DESCRIPTION

This product has been manufactured in Spain in accordance with the European standard EN13489. Product: Multi-Layered Engineered Hardwood Floor

COMPOSITION

Engineered for superior stability and durability, the structure combines a high-performance Marine-Grade Phenolic Birch Plywood core with a premium European Oak top layer. Both layers are bonded with polyvinyl acetate adhesives in accordance with CARB Phase 2 compliance standards.

DIMENSIONS

Total thickness (in) 5/8"
Top Layer thickness (mm) 4 mm (nominal)
Plywood thickness (mm) 12 mm
Length (ft) 6 - 8'
Width (in) 8"

DIMENSIONS TOLERANCES (EN 13647)

Length Nominal ± 0.1%
Width Nominal ± 0.2%
Cupping 0.2% of nominal width
Banana 0.1% nominal length

Length	6'	6.5'	7.2'	8'
Weight / box (lb)	33.85	35.10	37.60	47.60
Sq.ft. / box	15.75	17.5	19.22	21.41
Boxes / pallet	60	60	60	60
Weight / pallet	2085	2160	2310	2910
Sq.ft. / pallet	945	1050	1153.2	1284.6

GRADE

Prime, solid knots up to 10 mm permitted in less 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished Bona® Ultra Matt Lacquer
Impact Resistance Ø medium of deep 8.59 mm
Dimensional Stability (EN-1910): Movement ≤ 0.29%
Formaldehyde Emission (EN-120) E0. CARB2 Comply
Thermal conductivity (UNE-92-202) 0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8) ΔLw: 17 dB
Fire Reaction (UNE 23727) Cfl-S1
Profiling System Tongue & Groove, beveled 2 sides
Warranty www.rivaspain.com
Maintenance & Instructions www.rivaspain.com



RIVA\MAX

Smoke 10" Character
Color Width Grade



DESCRIPTION

This product has been manufactured in Spain in accordance with the European standard EN13489. Product: Multi-Layered Engineered Hardwood Floor

COMPOSITION

Engineered for superior stability and durability, the structure combines a high-performance Marine-Grade Phenolic Birch Plywood core with a premium European Oak top layer. Both layers are bonded with polyvinyl acetate adhesives in accordance with CARB Phase 2 compliance standards.

DIMENSIONS

Total thickness (in) 5/8"
Top Layer thickness (mm) 4 mm (nominal)
Plywood thickness (mm) 12 mm
Length (ft) 6 - 8'
Width (in) 8"

DIMENSIONS TOLERANCES (EN 13647)

Length Nominal ± 0.1%
Width Nominal ± 0.2%
Cupping 0.2% of nominal width
Banana 0.1% nominal length

Length	6'	6.5'	7.2'	8'
Weight / box (lb)	33.85	35.10	37.60	47.60
Sq.ft. / box	15.75	17.5	19.22	21.41
Boxes / pallet	60	60	60	60
Weight / pallet	2085	2160	2310	2910
Sq.ft. / pallet	945	1050	1153.2	1284.6

GRADE

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm). Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished Bona® Ultra Matt Lacquer
Impact Resistance Ø medium of deep 8.59 mm
Dimensional Stability (EN-1910): Movement ≤ 0.29%
Formaldehyde Emission (EN-120) E0. CARB2 Comply
Thermal conductivity (UNE-92-202) 0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8) ΔLw: 17 dB
Fire Reaction (UNE 23727) Cfl-S1
Profiling System Tongue & Groove, beveled 2 sides
Warranty www.rivaspain.com
Maintenance & Instructions www.rivaspain.com



RIVA\MAX

Mercury 10" Prime
Color Width Grade

DESCRIPTION

This product has been manufactured in Spain in accordance with the European standard EN13489. Product: Multi-Layered Engineered Hardwood Floor

COMPOSITION

Engineered for superior stability and durability, the structure combines a high-performance Marine-Grade Phenolic Birch Plywood core with a premium European Oak top layer. Both layers are bonded with polyvinyl acetate adhesives in accordance with CARB Phase 2 compliance standards.

DIMENSIONS

Total thickness (in) 5/8"
Top Layer thickness (mm) 4 mm (nominal)
Plywood thickness (mm) 12 mm
Length (ft) 6 - 8'
Width (in) 8"

DIMENSIONS TOLERANCES (EN 13647)

Length Nominal ± 0.1%
Width Nominal ± 0.2%
Cupping 0.2% of nominal width
Banana 0.1% nominal length

Length	6'	6.5'	7.2'	8'
Weight / box (lb)	33.85	35.10	37.60	47.60
Sq.ft. / box	15.75	17.5	19.22	21.41
Boxes / pallet	60	60	60	60
Weight / pallet	2085	2160	2310	2910
Sq.ft. / pallet	945	1050	1153.2	1284.6



GRADE

Prime, solid knots up to 10 mm permitted in less 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished Bona® Ultra Matt Lacquer
Impact Resistance Ø medium of deep 8.59 mm
Dimensional Stability (EN-1910): Movement ≤ 0.29%
Formaldehyde Emission (EN-120) E0. CARB2 Comply
Thermal conductivity (UNE-92-202) 0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8) ΔLw: 17 dB
Fire Reaction (UNE 23727) Cfl-S1
Profiling System Tongue & Groove, beveled 2 sides
Warranty www.rivaspain.com
Maintenance & Instructions www.rivaspain.com



RIVA\MAX

Mercury 10" Character
Color Width Grade



DESCRIPTION

This product has been manufactured in Spain in accordance with the European standard EN13489. Product: Multi-Layered Engineered Hardwood Floor

COMPOSITION

Engineered for superior stability and durability, the structure combines a high-performance Marine-Grade Phenolic Birch Plywood core with a premium European Oak top layer. Both layers are bonded with polyvinyl acetate adhesives in accordance with CARB Phase 2 compliance standards.

DIMENSIONS

Total thickness (in) 5/8"
Top Layer thickness (mm) 4 mm (nominal)
Plywood thickness (mm) 12 mm
Length (ft) 6 - 8'
Width (in) 8"

DIMENSIONS TOLERANCES (EN 13647)

Length Nominal ± 0.1%
Width Nominal ± 0.2%
Cupping 0.2% of nominal width
Banana 0.1% nominal length

Length	6'	6.5'	7.2'	8'
Weight / box (lb)	33.85	35.10	37.60	47.60
Sq.ft. / box	15.75	17.5	19.22	21.41
Boxes / pallet	60	60	60	60
Weight / pallet	2085	2160	2310	2910
Sq.ft. / pallet	945	1050	1153.2	1284.6

GRADE

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm). Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished Bona® Ultra Matt Lacquer
Impact Resistance Ø medium of deep 8.59 mm
Dimensional Stability (EN-1910): Movement ≤ 0.29%
Formaldehyde Emission (EN-120) E0. CARB2 Comply
Thermal conductivity (UNE-92-202) 0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8) ΔLw: 17 dB
Fire Reaction (UNE 23727) Cfl-S1
Profiling System Tongue & Groove, beveled 2 sides
Warranty www.rivaspain.com
Maintenance & Instructions www.rivaspain.com



RIVA\MAX

Sand 10" Prime
Color Width Grade



DESCRIPTION

This product has been manufactured in Spain in accordance with the European standard EN13489. Product: Multi-Layered Engineered Hardwood Floor

COMPOSITION

Engineered for superior stability and durability, the structure combines a high-performance Marine-Grade Phenolic Birch Plywood core with a premium European Oak top layer. Both layers are bonded with polyvinyl acetate adhesives in accordance with CARB Phase 2 compliance standards.

DIMENSIONS

Total thickness (in) 5/8"
Top Layer thickness (mm) 4 mm (nominal)
Plywood thickness (mm) 12 mm
Length (ft) 6 - 8'
Width (in) 8"

DIMENSIONS TOLERANCES (EN 13647)

Length Nominal ± 0.1%
Width Nominal ± 0.2%
Cupping 0.2% of nominal width
Banana 0.1% nominal length

Length	6'	6.5'	7.2'	8'
Weight / box (lb)	33.85	35.10	37.60	47.60
Sq.ft. / box	15.75	17.5	19.22	21.41
Boxes / pallet	60	60	60	60
Weight / pallet	2085	2160	2310	2910
Sq.ft. / pallet	945	1050	1153.2	1284.6

GRADE

Prime, solid knots up to 10 mm permitted in less 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished Bona® Ultra Matt Lacquer
Impact Resistance Ø medium of deep 8.59 mm
Dimensional Stability (EN-1910): Movement ≤ 0.29%
Formaldehyde Emission (EN-120) E0. CARB2 Comply
Thermal conductivity (UNE-92-202) 0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8) ΔLw: 17 dB
Fire Reaction (UNE 23727) Cfl-S1
Profiling System Tongue & Groove, beveled 2 sides
Warranty www.rivaspain.com
Maintenance & Instructions www.rivaspain.com



RIVA\MAX

Sand 10" Character
Color Width Grade



DESCRIPTION

This product has been manufactured in Spain in accordance with the European standard EN13489. Product: Multi-Layered Engineered Hardwood Floor

COMPOSITION

Engineered for superior stability and durability, the structure combines a high-performance Marine-Grade Phenolic Birch Plywood core with a premium European Oak top layer. Both layers are bonded with polyvinyl acetate adhesives in accordance with CARB Phase 2 compliance standards.

DIMENSIONS

Total thickness (in) 5/8"
Top Layer thickness (mm) 4 mm (nominal)
Plywood thickness (mm) 12 mm
Length (ft) 6 - 8'
Width (in) 8"

DIMENSIONS TOLERANCES (EN 13647)

Length Nominal ± 0.1%
Width Nominal ± 0.2%
Cupping 0.2% of nominal width
Banana 0.1% nominal length

Length	6'	6.5'	7.2'	8'
Weight / box (lb)	33.85	35.10	37.60	47.60
Sq.ft. / box	15.75	17.5	19.22	21.41
Boxes / pallet	60	60	60	60
Weight / pallet	2085	2160	2310	2910
Sq.ft. / pallet	945	1050	1153.2	1284.6

GRADE

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm). Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished Bona® Ultra Matt Lacquer
Impact Resistance Ø medium of deep 8.59 mm
Dimensional Stability (EN-1910): Movement ≤ 0.29%
Formaldehyde Emission (EN-120) E0. CARB2 Comply
Thermal conductivity (UNE-92-202) 0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8) ΔLw: 17 dB
Fire Reaction (UNE 23727) Cfl-S1
Profiling System Tongue & Groove, beveled 2 sides
Warranty www.rivaspain.com
Maintenance & Instructions www.rivaspain.com



RIVA\MAX

Earth 10" Prime
Color Width Grade



DESCRIPTION

This product has been manufactured in Spain in accordance with the European standard EN13489. Product: Multi-Layered Engineered Hardwood Floor

COMPOSITION

Engineered for superior stability and durability, the structure combines a high-performance Marine-Grade Phenolic Birch Plywood core with a premium European Oak top layer. Both layers are bonded with polyvinyl acetate adhesives in accordance with CARB Phase 2 compliance standards.

DIMENSIONS

Total thickness (in) 5/8"
Top Layer thickness (mm) 4 mm (nominal)
Plywood thickness (mm) 12 mm
Length (ft) 6 - 8'
Width (in) 8"

DIMENSIONS TOLERANCES (EN 13647)

Length Nominal ± 0.1%
Width Nominal ± 0.2%
Cupping 0.2% of nominal width
Banana 0.1% nominal length

Length	6'	6.5'	7.2'	8'
Weight / box (lb)	33.85	35.10	37.60	47.60
Sq.ft. / box	15.75	17.5	19.22	21.41
Boxes / pallet	60	60	60	60
Weight / pallet	2085	2160	2310	2910
Sq.ft. / pallet	945	1050	1153.2	1284.6

GRADE

Prime, solid knots up to 10 mm permitted in less 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished Bona® Ultra Matt Lacquer
Impact Resistance Ø medium of deep 8.59 mm
Dimensional Stability (EN-1910): Movement ≤ 0.29%
Formaldehyde Emission (EN-120) E0. CARB2 Comply
Thermal conductivity (UNE-92-202) 0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8) ΔLw: 17 dB
Fire Reaction (UNE 23727) Cfl-S1
Profiling System Tongue & Groove, beveled 2 sides
Warranty www.rivaspain.com
Maintenance & Instructions www.rivaspain.com



RIVA\MAX

Earth 10" Character
Color Width Grade



DESCRIPTION

This product has been manufactured in Spain in accordance with the European standard EN13489. Product: Multi-Layered Engineered Hardwood Floor

COMPOSITION

Engineered for superior stability and durability, the structure combines a high-performance Marine-Grade Phenolic Birch Plywood core with a premium European Oak top layer. Both layers are bonded with polyvinyl acetate adhesives in accordance with CARB Phase 2 compliance standards.

DIMENSIONS

Total thickness (in) 5/8"
Top Layer thickness (mm) 4 mm (nominal)
Plywood thickness (mm) 12 mm
Length (ft) 6 - 8'
Width (in) 8"

DIMENSIONS TOLERANCES (EN 13647)

Length Nominal ± 0.1%
Width Nominal ± 0.2%
Cupping 0.2% of nominal width
Banana 0.1% nominal length

Length	6'	6.5'	7.2'	8'
Weight / box (lb)	33.85	35.10	37.60	47.60
Sq.ft. / box	15.75	17.5	19.22	21.41
Boxes / pallet	60	60	60	60
Weight / pallet	2085	2160	2310	2910
Sq.ft. / pallet	945	1050	1153.2	1284.6

GRADE

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm). Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished Bona® Ultra Matt Lacquer
Impact Resistance Ø medium of deep 8.59 mm
Dimensional Stability (EN-1910): Movement ≤ 0.29%
Formaldehyde Emission (EN-120) E0. CARB2 Comply
Thermal conductivity (UNE-92-202) 0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8) ΔLw: 17 dB
Fire Reaction (UNE 23727) Cfl-S1
Profiling System Tongue & Groove, beveled 2 sides
Warranty www.rivaspain.com
Maintenance & Instructions www.rivaspain.com



RIVA\MAX

Krypton 10" Prime
Color Width Grade



DESCRIPTION

This product has been manufactured in Spain in accordance with the European standard EN13489. Product: Multi-Layered Engineered Hardwood Floor

COMPOSITION

Engineered for superior stability and durability, the structure combines a high-performance Marine-Grade Phenolic Birch Plywood core with a premium European Oak top layer. Both layers are bonded with polyvinyl acetate adhesives in accordance with CARB Phase 2 compliance standards.

DIMENSIONS

Total thickness (in) 5/8"
Top Layer thickness (mm) 4 mm (nominal)
Plywood thickness (mm) 12 mm
Length (ft) 6 - 8'
Width (in) 8"

DIMENSIONS TOLERANCES (EN 13647)

Length Nominal ± 0.1%
Width Nominal ± 0.2%
Cupping 0.2% of nominal width
Banana 0.1% nominal length

Length	6'	6.5'	7.2'	8'
Weight / box (lb)	33.85	35.10	37.60	47.60
Sq.ft. / box	15.75	17.5	19.22	21.41
Boxes / pallet	60	60	60	60
Weight / pallet	2085	2160	2310	2910
Sq.ft. / pallet	945	1050	1153.2	1284.6

GRADE

Prime, solid knots up to 10 mm permitted in less 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished Bona® Ultra Matt Lacquer
Impact Resistance Ø medium of deep 8.59 mm
Dimensional Stability (EN-1910): Movement ≤ 0.29%
Formaldehyde Emission (EN-120) E0. CARB2 Comply
Thermal conductivity (UNE-92-202) 0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8) ΔLw: 17 dB
Fire Reaction (UNE 23727) Cfl-S1
Profiling System Tongue & Groove, beveled 2 sides
Warranty www.rivaspain.com
Maintenance & Instructions www.rivaspain.com



RIVA\MAX

Krypton 10" Character
Color Width Grade



DESCRIPTION

This product has been manufactured in Spain in accordance with the European standard EN13489. Product: Multi-Layered Engineered Hardwood Floor

COMPOSITION

Engineered for superior stability and durability, the structure combines a high-performance Marine-Grade Phenolic Birch Plywood core with a premium European Oak top layer. Both layers are bonded with polyvinyl acetate adhesives in accordance with CARB Phase 2 compliance standards.

DIMENSIONS

Total thickness (in) 5/8"
Top Layer thickness (mm) 4 mm (nominal)
Plywood thickness (mm) 12 mm
Length (ft) 6 - 8'
Width (in) 8"

DIMENSIONS TOLERANCES (EN 13647)

Length Nominal ± 0.1%
Width Nominal ± 0.2%
Cupping 0.2% of nominal width
Banana 0.1% nominal length

Length	6'	6.5'	7.2'	8'
Weight / box (lb)	33.85	35.10	37.60	47.60
Sq.ft. / box	15.75	17.5	19.22	21.41
Boxes / pallet	60	60	60	60
Weight / pallet	2085	2160	2310	2910
Sq.ft. / pallet	945	1050	1153.2	1284.6

GRADE

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm). Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished Bona® Ultra Matt Lacquer
Impact Resistance Ø medium of deep 8.59 mm
Dimensional Stability (EN-1910): Movement ≤ 0.29%
Formaldehyde Emission (EN-120) E0. CARB2 Comply
Thermal conductivity (UNE-92-202) 0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8) ΔLw: 17 dB
Fire Reaction (UNE 23727) Cfl-S1
Profiling System Tongue & Groove, beveled 2 sides
Warranty www.rivaspain.com
Maintenance & Instructions www.rivaspain.com



RIVA\MAX

Amber 10" Prime
Color Width Grade



DESCRIPTION

This product has been manufactured in Spain in accordance with the European standard EN13489. Product: Multi-Layered Engineered Hardwood Floor

COMPOSITION

Engineered for superior stability and durability, the structure combines a high-performance Marine-Grade Phenolic Birch Plywood core with a premium European Oak top layer. Both layers are bonded with polyvinyl acetate adhesives in accordance with CARB Phase 2 compliance standards.

DIMENSIONS

Total thickness (in) 5/8"
Top Layer thickness (mm) 4 mm (nominal)
Plywood thickness (mm) 12 mm
Length (ft) 6 - 8'
Width (in) 8"

DIMENSIONS TOLERANCES (EN 13647)

Length Nominal ± 0.1%
Width Nominal ± 0.2%
Cupping 0.2% of nominal width
Banana 0.1% nominal length

Length	6'	6.5'	7.2'	8'
Weight / box (lb)	33.85	35.10	37.60	47.60
Sq.ft. / box	15.75	17.5	19.22	21.41
Boxes / pallet	60	60	60	60
Weight / pallet	2085	2160	2310	2910
Sq.ft. / pallet	945	1050	1153.2	1284.6

GRADE

Prime, solid knots up to 10 mm permitted in less 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished Bona® Ultra Matt Lacquer
Impact Resistance Ø medium of deep 8.59 mm
Dimensional Stability (EN-1910): Movement ≤ 0.29%
Formaldehyde Emission (EN-120) E0. CARB2 Comply
Thermal conductivity (UNE-92-202) 0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8) ΔLw: 17 dB
Fire Reaction (UNE 23727) Cfl-S1
Profiling System Tongue & Groove, beveled 2 sides
Warranty www.rivaspain.com
Maintenance & Instructions www.rivaspain.com



RIVA\MAX

Amber 10" Character
Color Width Grade



DESCRIPTION

This product has been manufactured in Spain in accordance with the European standard EN13489. Product: Multi-Layered Engineered Hardwood Floor

COMPOSITION

Engineered for superior stability and durability, the structure combines a high-performance Marine-Grade Phenolic Birch Plywood core with a premium European Oak top layer. Both layers are bonded with polyvinyl acetate adhesives in accordance with CARB Phase 2 compliance standards.

DIMENSIONS

Total thickness (in) 5/8"
Top Layer thickness (mm) 4 mm (nominal)
Plywood thickness (mm) 12 mm
Length (ft) 6 - 8'
Width (in) 8"

DIMENSIONS TOLERANCES (EN 13647)

Length Nominal ± 0.1%
Width Nominal ± 0.2%
Cupping 0.2% of nominal width
Banana 0.1% nominal length

Length	6'	6.5'	7.2'	8'
Weight / box (lb)	33.85	35.10	37.60	47.60
Sq.ft. / box	15.75	17.5	19.22	21.41
Boxes / pallet	60	60	60	60
Weight / pallet	2085	2160	2310	2910
Sq.ft. / pallet	945	1050	1153.2	1284.6

GRADE

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm). Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished Bona® Ultra Matt Lacquer
Impact Resistance Ø medium of deep 8.59 mm
Dimensional Stability (EN-1910): Movement ≤ 0.29%
Formaldehyde Emission (EN-120) E0. CARB2 Comply
Thermal conductivity (UNE-92-202) 0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8) ΔLw: 17 dB
Fire Reaction (UNE 23727) Cfl-S1
Profiling System Tongue & Groove, beveled 2 sides
Warranty www.rivaspain.com
Maintenance & Instructions www.rivaspain.com



RIVA\MAX

Cigar 10" Prime
Color Width Grade



DESCRIPTION

This product has been manufactured in Spain in accordance with the European standard EN13489. Product: Multi-Layered Engineered Hardwood Floor

COMPOSITION

Engineered for superior stability and durability, the structure combines a high-performance Marine-Grade Phenolic Birch Plywood core with a premium European Oak top layer. Both layers are bonded with polyvinyl acetate adhesives in accordance with CARB Phase 2 compliance standards.

DIMENSIONS

Total thickness (in) 5/8"
Top Layer thickness (mm) 4 mm (nominal)
Plywood thickness (mm) 12 mm
Length (ft) 6 - 8'
Width (in) 8"

DIMENSIONS TOLERANCES (EN 13647)

Length Nominal ± 0.1%
Width Nominal ± 0.2%
Cupping 0.2% of nominal width
Banana 0.1% nominal length

Length	6'	6.5'	7.2'	8'
Weight / box (lb)	33.85	35.10	37.60	47.60
Sq.ft. / box	15.75	17.5	19.22	21.41
Boxes / pallet	60	60	60	60
Weight / pallet	2085	2160	2310	2910
Sq.ft. / pallet	945	1050	1153.2	1284.6

GRADE

Prime, solid knots up to 10 mm permitted in less 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished Bona® Ultra Matt Lacquer
Impact Resistance Ø medium of deep 8.59 mm
Dimensional Stability (EN-1910): Movement ≤ 0.29%
Formaldehyde Emission (EN-120) E0. CARB2 Comply
Thermal conductivity (UNE-92-202) 0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8) ΔLw: 17 dB
Fire Reaction (UNE 23727) Cfl-S1
Profiling System Tongue & Groove, beveled 2 sides
Warranty www.rivaspain.com
Maintenance & Instructions www.rivaspain.com



RIVA\MAX

Cigar 10" Character
Color Width Grade



DESCRIPTION

This product has been manufactured in Spain in accordance with the European standard EN13489. Product: Multi-Layered Engineered Hardwood Floor

COMPOSITION

Engineered for superior stability and durability, the structure combines a high-performance Marine-Grade Phenolic Birch Plywood core with a premium European Oak top layer. Both layers are bonded with polyvinyl acetate adhesives in accordance with CARB Phase 2 compliance standards.

DIMENSIONS

Total thickness (in) 5/8"
Top Layer thickness (mm) 4 mm (nominal)
Plywood thickness (mm) 12 mm
Length (ft) 6 - 8'
Width (in) 8"

DIMENSIONS TOLERANCES (EN 13647)

Length Nominal ± 0.1%
Width Nominal ± 0.2%
Cupping 0.2% of nominal width
Banana 0.1% nominal length

Length	6'	6.5'	7.2'	8'
Weight / box (lb)	33.85	35.10	37.60	47.60
Sq.ft. / box	15.75	17.5	19.22	21.41
Boxes / pallet	60	60	60	60
Weight / pallet	2085	2160	2310	2910
Sq.ft. / pallet	945	1050	1153.2	1284.6

GRADE

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm). Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished Bona® Ultra Matt Lacquer
Impact Resistance Ø medium of deep 8.59 mm
Dimensional Stability (EN-1910): Movement ≤ 0.29%
Formaldehyde Emission (EN-120) E0. CARB2 Comply
Thermal conductivity (UNE-92-202) 0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8) ΔLw: 17 dB
Fire Reaction (UNE 23727) Cfl-S1
Profiling System Tongue & Groove, beveled 2 sides
Warranty www.rivaspain.com
Maintenance & Instructions www.rivaspain.com

