

RIVA \ METRO

Crystal 6 3/4" Character
Color **Width** **Grade**



DESCRIPTION

This product has been manufactured in Spain in accordance with the European standard EN13489. Product: Multi-Layered Engineered Hardwood Floor

COMPOSITION

Engineered for superior stability and durability, the structure combines a high-performance Marine-Grade Phenolic Birch Plywood core with a premium European Oak top layer. Both layers are bonded with polyvinyl acetate adhesives in accordance with CARB Phase 2 compliance standards.

DIMENSIONS

Total thickness (in) 5/8"
Top Layer thickness (mm) 4 mm (nominal)
Plywood thickness (mm) 12 mm
Length (ft) 6 - 8'
Width (in) 6 3/4"

DIMENSIONS TOLERANCES (EN 13647)

Length Nominal ± 0.1%
Width Nominal ± 0.2%
Cupping 0.2% of nominal width
Banana 0.1% nominal length

Length	6'	6.5'	7.2'	8'
Weight / box (lb)	26.89	27.38	37.44	38.90
Sq.ft. / box	13.16	14.63	16.1	17.6
Boxes / pallet	72	72	72	72
Weight / pallet	1990	2025	2750	2850
Sq.ft. / pallet	947.52	1053.36	1159.2	1276.2

GRADE

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm). Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished Bona® Ultra Matt Lacquer
Impact Resistance Ø medium of deep 8.59 mm
Dimensional Stability (EN-1910): Movement ≤ 0.29%
Formaldehyde Emission (EN-120) E0. CARB2 Comply
Thermal conductivity (UNE-92-202) 0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8) ΔLw: 17 dB
Fire Reaction (UNE 23727) Cfl-S1
Profiling System Tongue & Groove, beveled 2 sides
Warranty www.rivaspain.com
Maintenance & Instructions www.rivaspain.com



RIVA \ METRO

Pearl 6 3/4" Character
Color **Width** **Grade**



DESCRIPTION

This product has been manufactured in Spain in accordance with the European standard EN13489. Product: Multi-Layered Engineered Hardwood Floor

COMPOSITION

Engineered for superior stability and durability, the structure combines a high-performance Marine-Grade Phenolic Birch Plywood core with a premium European Oak top layer. Both layers are bonded with polyvinyl acetate adhesives in accordance with CARB Phase 2 compliance standards.

DIMENSIONS

Total thickness (in) 5/8"
Top Layer thickness (mm) 4 mm (nominal)
Plywood thickness (mm) 12 mm
Length (ft) 6 - 8'
Width (in) 6 3/4"

DIMENSIONS TOLERANCES (EN 13647)

Length Nominal ± 0.1%
Width Nominal ± 0.2%
Cupping 0.2% of nominal width
Banana 0.1% nominal length

Length	6'	6.5'	7.2'	8'
Weight / box (lb)	26.89	27.38	37.44	38.90
Sq.ft. / box	13.16	14.63	16.1	17.6
Boxes / pallet	72	72	72	72
Weight / pallet	1990	2025	2750	2850
Sq.ft. / pallet	947.52	1053.36	1159.2	1276.2

GRADE

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm). Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished Bona® Ultra Matt Lacquer
Impact Resistance Ø medium of deep 8.59 mm
Dimensional Stability (EN-1910): Movement ≤ 0.29%
Formaldehyde Emission (EN-120) E0. CARB2 Comply
Thermal conductivity (UNE-92-202) 0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8) ΔLw: 17 dB
Fire Reaction (UNE 23727) Cfl-S1
Profiling System Tongue & Groove, beveled 2 sides
Warranty www.rivaspain.com
Maintenance & Instructions www.rivaspain.com



RIVA \ METRO

Cotton 6 3/4" Character
Color **Width** **Grade**



DESCRIPTION

This product has been manufactured in Spain in accordance with the European standard EN13489. Product: Multi-Layered Engineered Hardwood Floor

COMPOSITION

Engineered for superior stability and durability, the structure combines a high-performance Marine-Grade Phenolic Birch Plywood core with a premium European Oak top layer. Both layers are bonded with polyvinyl acetate adhesives in accordance with CARB Phase 2 compliance standards.

DIMENSIONS

Total thickness (in) 5/8"
Top Layer thickness (mm) 4 mm (nominal)
Plywood thickness (mm) 12 mm
Length (ft) 6 - 8'
Width (in) 6 3/4"

DIMENSIONS TOLERANCES (EN 13647)

Length Nominal ± 0.1%
Width Nominal ± 0.2%
Cupping 0.2% of nominal width
Banana 0.1% nominal length

Length	6'	6.5'	7.2'	8'
Weight / box (lb)	26.89	27.38	37.44	38.90
Sq.ft. / box	13.16	14.63	16.1	17.6
Boxes / pallet	72	72	72	72
Weight / pallet	1990	2025	2750	2850
Sq.ft. / pallet	947.52	1053.36	1159.2	1276.2

GRADE

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm). Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished Bona® Ultra Matt Lacquer
Impact Resistance Ø medium of deep 8.59 mm
Dimensional Stability (EN-1910): Movement ≤ 0.29%
Formaldehyde Emission (EN-120) E0. CARB2 Comply
Thermal conductivity (UNE-92-202) 0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8) ΔLw: 17 dB
Fire Reaction (UNE 23727) Cfl-S1
Profiling System Tongue & Groove, beveled 2 sides
Warranty www.rivaspain.com
Maintenance & Instructions www.rivaspain.com



RIVA \ METRO

Smoke 6 3/4" Character
Color Width Grade



DESCRIPTION

This product has been manufactured in Spain in accordance with the European standard EN13489. Product: Multi-Layered Engineered Hardwood Floor

COMPOSITION

Engineered for superior stability and durability, the structure combines a high-performance Marine-Grade Phenolic Birch Plywood core with a premium European Oak top layer. Both layers are bonded with polyvinyl acetate adhesives in accordance with CARB Phase 2 compliance standards.

DIMENSIONS

Total thickness (in) 5/8"
Top Layer thickness (mm) 4 mm (nominal)
Plywood thickness (mm) 12 mm
Length (ft) 6 - 8'
Width (in) 6 3/4"

DIMENSIONS TOLERANCES (EN 13647)

Length Nominal ± 0.1%
Width Nominal ± 0.2%
Cupping 0.2% of nominal width
Banana 0.1% nominal length

Length	6'	6.5'	7.2'	8'
Weight / box (lb)	26.89	27.38	37.44	38.90
Sq.ft. / box	13.16	14.63	16.1	17.6
Boxes / pallet	72	72	72	72
Weight / pallet	1990	2025	2750	2850
Sq.ft. / pallet	947.52	1053.36	1159.2	1276.2

GRADE

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm). Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished Bona® Ultra Matt Lacquer
Impact Resistance Ø medium of deep 8.59 mm
Dimensional Stability (EN-1910): Movement ≤ 0.29%
Formaldehyde Emission (EN-120) E0. CARB2 Comply
Thermal conductivity (UNE-92-202) 0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8) ΔLw: 17 dB
Fire Reaction (UNE 23727) Cfl-S1
Profiling System Tongue & Groove, beveled 2 sides
Warranty www.rivaspain.com
Maintenance & Instructions www.rivaspain.com

